

EP22A Digital Podium

Professional Podium

Complex presentations that require multiple additional devices, communication and power ports, AV control panels, EP22A covers all of them. Professional and more technical meetings, conferences and classes are the places for EP22A. Well designed, dedicated work-areas on top surface allows the speaker to make the presentation neat and tidy.

EP22A

- 22" Top screen with IR touch technology
- Professional microphones
- Exquisite and elegant
- Superior materials, firm and durable
- Multiple color options
- Built in high performance PC.



Wide touch screen designed with IPS technology. Multiple types of connectors for complex purpose and controls. Steady work place for documents and additional devices.



Slim design, appropriate standing position



Multiple connectors to connect existing devices at the hall. Protection cover.



Well balanced, durable, wide body

Technical Specifications



Model Name:

ML22T

EP22A

Front Panel		
Screen Specifications		
Resolution	-	-
Brightness	-	-
Aspect ratio	-	-
Front Panel PC Specifications	-	-
Lecturer Panel	21,5"	21,5"
Screen Specifications		
Resolution	1920x1080 FHD	1920x1080 FHD
Brightness	250 cd/m2	250 cd/m2
Aspect ratio	16:9	16:9
Touch Screen Technology	Capacitive	Infrared
Touch Points	10 points	Dual Touch
Lecturer Panel PC Specifications	4th i3 - 4 GB /120 GB - Windows IoT	4th i3 - 4 GB /120 GB - Windows IoT
Microphone		
Length	18"	18"
No of microphone	1 pcs	2 pcs
Output Connector	3-way XLR (Male)	3-way XLR (Male)
Microphone Type	Cardioid	Cardioid
Frequency Response	50 -18 kHz	50 -18 kHz
Sensitivity (at 1,000Hz)	-60dB ± 3dB	-60dB ± 3dB
Impedance	220Ω	220Ω
Power ON indicator	LED	LED
Power requirement	Phantom Power (48V)	2 x Phantom Power (48V)
Inputs		
VGA	Available (On desk for Laptop)	Available (On desk for Laptop)
Sound	3,5mm jak (On desk for Laptop)	3,5mm jak (On desk for Laptop)
HDMI	Available (On desk for Laptop)	Available (On desk for Laptop)
Ethernet	Available (On desk for Laptop)	Available (On desk for Laptop)
230V Plug (Max 5A)	Available (On desk for Laptop / mobile phone charge)	Available (On desk for Laptop / mobile phone charge)
USB	USB 2.0 x 4 (On desk for internal PC)	USB 2.0 x 4 (On desk for internal PC)
Outputs (Bottom of)		
VGA	Optional (For old type projectors)	Optional (For old type projectors)
HDMI	Available (Projector Out) (max output 1080p)	Available (Projector Out) (max output 1080p)
RS232	For Projector On/Off	For Projector On/Off
Ethernet 1	Network Connection for Complete System Optional	Network Connection for Complete System Optional
Ethernet 2	(Network Connection for HDBaseT Projector)	(Network Connection for HDBaseT Projector)
Ethernet for Control of External Device	Network Connection for Device Control	
Amplifier		
Speaker impedans	2x 4Ω Speakers	2x 4Ω Speakers
Sound Output power	2x 20W	2x 20W
Total Harmonic Distorsion	1,01	1,01
Signal/Noise Ratio	80dB	80dB
Frequency range	20Hz to 20kHz	20Hz to 20kHz
Stereo Channel Separation	>75dB	>75dB
Ipad Control		
On/Off	Available	
Volume control	Available	N/A
Input Selction	Available	N/A
Projector / Display	Available	N/A
Turn Outputs On and off	Available	
Power		
Power Input	230V 50Hz	230V 50Hz
Power Consumption	375W (max)	375W (max)