



DL22A Digital Podium Detailed Specifications

Model:	DL22A	DL22A-M
		
Main Specifications		
Speaker Screen	22" Multi touch capacitive	22" Multi touch capacitive
Front Screen	22" with built-in signage media player	22" with built-in signage media player
Built-in PC for Speaker Screen	intel i3 4GB Ram, 120 GB SSD, Win 10 Embedded IoT	intel i3 4GB Ram, 120 GB SSD, Win 10 Embedded IoT
Microphone	2 pcs 18" Gooseneck Condenser Microphone	2 pcs 18" Gooseneck Condenser Microphone
Lifting Column	Not available	Available
Detailed Specifications		
Front Panel	22"	22"
Screen Specifications		
Resolution	1920x1080 FHD	1920x1080 FHD
Brightness	250 cd/m ²	250 cd/m ²
Aspect ratio	16:9	16:9
Panel Type	IPS	IPS
Front Panel Player	Built-in Digital Signage Media Player	Built-in Digital Signage Media Player
Front Panel Content Management Software	Available	Available
Lecturer Panel	22"	22"
Screen Specifications		
Resolution	1920x1080 FHD	1920x1080 FHD
Brightness	250 cd/m ²	250 cd/m ²
Panel Type	IPS	IPS
Aspect ratio	16:9	16:9
Touch Technology	Capacitive	Capacitive
Touch Points	10 points	10 points
Lecturer Panel PC Specifications		
CPU	4th Generation Intel Core i3	4th Generation Intel Core i3
RAM	4 GB DDR4	4 GB DDR4
HDD	120 GB SSD	120 GB SSD
Operating System	Windows Embedded 10 IoT	Windows Embedded 10 IoT
Microphone		
Length	18"	18"
No of microphone	2 pcs	2 pcs
Output Connector	3-way XLR (Male)	3-way XLR (Male)
Microphone Type	Cardioid	Cardioid
Frequency Response	50 -18 kHz	50 -18 kHz
Sensitivity (at 1,000Hz)	-60dB ± 3dB	-60dB ± 3dB
Impedance	220Ω	220Ω
Power ON indicator	LED	LED
Power requirement	2 x Phantom Power (48V)	2 x Phantom Power (48V)
Inputs (on Speaker Panel)		
230V Plug (Max 5A)	Available	Available
USB	USB 2.0 x 4 (for internal PC)	USB 2.0 x 4 (for internal PC)
Outputs (Bottom of Podium)		
VGA	Available	Available
HDMI	Available	Available
Ethernet	Available	Available
XLR for microphone	Available	Available
USB	USB 2.0 x 2 (for internal PC)	USB 2.0 x 2 (for internal PC)
Height Adjust Engine		
Movement	N/A	Vertical (Up/Down)
Control	N/A	By Buttons (Up/Down)
Speed	N/A	Max speed: 38 mm/s
Lifting strength	N/A	700N
Locking System	N/A	Automatic Locking when engine not working
Engine Type	N/A	Electrical
Power		
Power Input	230V 50Hz	230V 50Hz
Power Consumption	400W (max)	450W (max)
Peripherals & other features		
Clock & Timer	Available	Available
Color	Black speaker panel and base, gray body	Black speaker panel and base, grey body
Packing	Wooden box export packing	Wooden box export packing
Mechanical Specs		
Outline Dimension (mm)	Set: 550 x 800 x 1091 Package: 670 x 920 x 1300	Set: 550 x 800 x 1091 Package: 670 x 920 x 1300
Weight (kg)	Set: 68 kg Package: 107 kg	Set: 68 kg Package: 107 kg
Optional features	Front screen PC Flight case	Front screen PC Flight case