

Z Series 13" | 32"

Hand Sanitizer Dispenser Kiosk



cletech

TECHNOLOGICAL SOLUTION AGAINST COVID-19

We strive hard to minimize the effects of Covid 19 and remaining sterile at all times. As Cletech, we developed a new product with an automatic hand sanitizer system to make our life easier in this period.

The kiosk, which provides to inform and directing on the screen, also has a structure that can automatically dispense the hand sanitizer solution from the bottom part. It can be used easily in public areas such as Shopping Mall, Store, Hospital, Restaurant with its stylish design.



ZSD32N 32"



ZSD13N 13"

TECHNICAL SPECIFICATIONS

		ZSD13N	ZSD32N
SPECIFICATIONS			
MONITOR	Monitor	Samsung QB13R	Samsung DM32E
	Display	Edge LED LCD Panel	D-LED BLU LCD Panel
	Display Size	13" (Diagonal)	32" (Diagonal)
	Active Area	294 x 165 mm	393 x 698 mm
	Resolution	Full HD, 1920 x 1080 px	Full HD, 1920 x 1080 px
	Brightness	300 cd/m ²	400 cd/m ²
	Contrast	800:1	5000:1
	Response Time	8 ms	8 ms
	Viewing Angle	89°/89°/89°/89° (Ü/A/S/S)	89°/89°/89°/89° (Ü/A/S/S)
	Operating Temp.	0°C ~ 40°C	0°C ~ 40°C
	Operation Hour	7/16	7/24
	Lifetime	50.000 Hours	50.000 Hours
	Speaker	1 x 5 Watt (Stereo)	2 x 10 Watt (Stereo)
	Processor	Cortex A72 1.7GHz Quad-Core CPU	Cortex-A9 1GHz Quad Core CPU
MEDIA PLAYER	Graphic	Graphic Resolution: 3840x2160	Graphic Resolution: 1920x1080
	Memory	2.5GB LPDDR4 1.5GHz 64bit	1.5GB Dual 48bit DDR3
	Storage	8GB (3.88GB Op. Sys., 4.12GB Ava.)	8GB (2.65GB Op. Sys., 5.35GB Ava.)
	Network	10/100M Wired, 2.4 G Wireless	10/100M Wired, 2.4 G Wireless
DIMENSIONS	Operating System	Tizen 4.0 (VDLinux)	Tizen 3.0 (VDLinux)
	Application	MagicInfo S6 ve SSSP 6.0	MagicInfo S3 ve SSSP 3.0
	Housing (WxHxD)	413 x 1600 x 205 mm	830 x 1840 x 120 mm
	Flange (WxD)	413 x 350 mm	832 x 400 mm
ENCLOSURE	Weight	45 kg	61 kg
	Packaging (WxHxD)	700 x 1650 x 260 mm	900 x 1890 x 170 mm
	Materials	Lightweight aluminum profile & steel	
	Surface	4mm safety tempered extra clear glass	
POWER	Coating	Electrostatic powder coating	
	Mounting	Connection holes for fixing to floor from inside	
	Dispenser	1 liter tank, automatic sanitizer spray with LED light	
	Distribution	3 Input Industrial Current Protected PDU	
POWER	Operating Voltage	110 - 240 VAC - 50/60 Hz	110 - 240 VAC - 50/60 Hz
	Energy Consump.	≤ 28 Watt (max)	≤ 77 Watt (max)
	Sleep Mode	≤ 1 Watt	≤ 1 Watt

cletech

Digital Signage Solutions



Europe
203 Rue Michel Carre
F-95870 BEZONS FRANCE
Tel : +33 (0)1 85 11 06 65
E-mail: commercial@osf-av.fr
Web: www.osf-av.com