

# iWall

409R




- 4K 60Hz Ultra HD video wall controller
- With 3.5mm audio output
- Input/ Outputs: 4x HDMI inputs (1x 4K@60Hz, 3x 4K@30Hz), 1x DP input (4K@60Hz), 9x HDMI outputs (1080p@60Hz), and 1x DP loop out.
- Supports cascading
- Multiple displaying modes: single image, PIP (Picture in Picture), POP (Picture on Picture), PYP (Picture by Picture: Up-Down or Left-Right side by side), or Quad-view.
- Supports matrix model (single display mode 1x1).
- Setup Free: Support IR remote control and serial RS232 control.- Support 90 degree portrait display or 180 degrees rotation
- FPGA technology, pure hardware real-time processing architecture without delay.




# Pure Hardware without Windows OS

Without Window blue screen, virus risks, OS vulnerability, and breakdown.  
Lower requirements of IT technology background, save your training cost.



## Multiple Videowall Layouts

It supports 1x3, 2x2, 2x3, 2x4, 3x2, 3x3, 4x2 and more video wall layouts of 3x6 or 3x9 by cascading another 409R.



## Multiple content layouts

It supports up to 5x sources (4x HDMI and 1x DisplayPort Inputs) displaying on the video wall by multiple windows layouts: PIP (Picture in Picture), POP (Picture on Picture), PYP (Picture by Picture: Up-Down or Left-Right side by side) or Quad-view.



# Setup Free


It can be controlled by the IR remote, without settings required. No set-up and just the simple click-and-display experience. It also supports RS232 control by the third-party device.



## 2K FHD TO 4K UHD


It supports crystal clear 4K60 UHD content and backwards compatible with 4K30 and 1080p.

2K



4K

## Diagram



# Datasheet

Product Name	iWall 409R
DisplayPort input	1x Display port 1.2 (3840×2160@60Hz)
HDMI inputs	1x HDMI 2.0 (3840×2160@60H)- HDMI IN 4 3x HDMI 1.4 (3840×2160@30H)- HDMI IN 1-3
HDMI outputs	9x HDMI 1.3 (1920*1080@60Hz)
Loop-out	1x Display port 1.2 (3840×2160@60Hz)
Audio output	1x 3.5mm
Control	Remote control, RS232
Factory default resolution	HDMI: 3840*2160@30Hz; DP: 3840*2160@60Hz
Support custom resolution	Yes
Operating temperature	0°C-50°C
Power consumption	12W
Power supply	12V@2A AC-DC
Net Weight	840g
Size	270*122.5*20mm WDH
Package list	One DP Cable; One 12V@2A AC-DC; One remote control
Warranty	One year



[www.osf-av.com](http://www.osf-av.com)



[commercial@osf-av.fr](mailto:commercial@osf-av.fr)



01 85 11 06 65

