

# iSpeaker

## USB Omnidirectional Speakerphone

USB / Portable / Plug and Play Model: iSpeaker M200



- |  |  |  |   |  |  |
|--|--|--|---|--|--|
| <b>Excellent Audio</b><br>HD, full duplex audio solution | <b>Plug and play</b><br>Universal USB connection | <b>Portable design</b><br>Easy to carry, for small and medium-sized meetings | <b>360° Pickup</b><br>360° omni-directional pickup. | <b>Dust-proof</b><br>More dust-proof and more durable. | <b>3.5mm Out</b><br>For mobile phones or other analog devices. |
|--|--|--|---|--|--|

- iSpeaker M200: USB Omnidirectional Speakerphone
- USB / Portable / Plug and Play
- Portable design: Easy to carry, small and medium-sized meetings will be launched at any time.
- Dynamic Speech: Microphone dynamic speech enhancement technology.
- 3.5mm Out: The 3.5mm interface can be used for mobile phones or other analog devices.
- Excellent Audio: HD, a full-duplex audio solution
- High-definition: Adaptive high-definition amplification technology
- Plug and play: support universal USB and connection
- Low consumption: Low power consumption design
- 360° Pickup: 360 degrees omni directional pickup, plug and play
- Dust-proof: The inductive button design is more dust-proof and more durable.



# Datasheet

<b>Model</b>	<b>iSpeaker M200</b>
<b>Name</b>	<b>USB omnidirectional Speakerphone</b>
Covering area	15-30m <sup>2</sup> , 160-320 square feet
Number of participants	6-12 participants
Microphone Pickup Distance	6m or 20 ft
Frequency response	50Hz-169kHz
Directivity	Omnidirectional
Noise Level	85dBA
Compatibility	Compatible with mainstream operating systems, like Microsoft Windows XP/Vista/7/8/10, Android, macOS, Linux, etc.
Full-duplex echo cancellation	support
Noise suppression	support
Gain control	support
Echo tail length	300ms
Power supply	USB:5 V DC @ 450 mA Maximum
Ports	1 x Micro USB data communication ; 1 x 3.5mm audio port
Packaging dimension (R x H)	75mm x30mm
Net weight	0.48 kg
Working temperature	0° to 40°C (+32° to 104°F)
Relative humidity	20% to 85% (non-condensing)
Storage temperature	-30° to +55°C (-22° to +131°F)

