

iMeeting H61

HDMI 4K 6x1 Multi-format Presentation Switcher



HDMI 1.4

Auto-detect

Auto Switch

10.2Gbps

4K30

HDR

Dolby Vision

HDCP 2.2

- Supports Lightning, USB-C, MINI DP, DP and Type-A HDMI input signal to be converted to HDMI signal.
- Auto-detects the input signal, the last connected signal source will be switched to the output automatically.
- Starts to scan from Lightning to Type-A HDMI and switch the first detected source to the output.
- Supports HDMI, DP and USB-C input video resolution up to 4Kx2K@30Hz.
- Supports HDMI output video resolutions up to 4Kx2K@30Hz 4:4:4.
- The Lightning device can be powered over the Lightning cable.



Datasheet

Input	
Connector Type	(1) Lighting, (1) USB Type-C, (1) Mini DP, (1) DP, (2) Type-A HDMI
Lighting Video Resolution	Up to 1080P@60Hz
USB-C Video Resolution	Up to 4Kx2K@30Hz
DP Video Resolution	Up to 4Kx2K@30Hz
HDMI Video Resolution	Up to 4Kx2K@30Hz
HDMI Version	1.4
HDCP Version	2.2
Video Bandwidth	10.2Gbps

Output	
Connector Type	HDMI Type-A
HDMI Version	1.4
HDCP Version	1.4
Output Video Resolution	Up to 4Kx2K@30Hz 4:4:4

General	
Operation Temperature	-10°C ~ +55°C
Storage Temperature	-25°C ~ +70°C
Relative Humidity	10% ~ 90%
Input Power	24V DC 1.25A
AC Adapter Input Power	100 ~ 240V AC, 50/60 Hz
Dimension (W*H*D)	135mm x 135mm x 30mm, Cable Length:1.3m
Net Weight	690g (Including cables)



www.osf-av.com



commercial@osf-av.fr



01 85 11 06 65

