


TW23P

TW23P is designed to satisfy the requirements in conference halls and hotels. Connecting projectors and audio systems to TW23P from its built-in connectors is easy. TW23P has latest technology for meeting rooms, and lecture halls. It is equipped with person's computer 32" front screen. It is also designed to be used as a stand alone product



-  TOUCH SCREEN
-  32"
-  22"
-  WI-FI
-  PLUG IN PLAY
-  TIMER



	TW23P	TW23P-A
Multi touch speaker screen	22"	22"
Front Screen with Embedded Signage Media Player	32"	✘
Remotely Controlled Electrical Lifting Column for Height Adjustment	●	●
Player PC : Intel i3 4GB, I20 SSD, Windows 10 Pro	●	●
Microphone	●	●
3.5" Digital Touch Timer	●	●
Creapen Annotation Software	●	●

TW23P

CONNECTIVITY IN



- 1 - 18"Shure Microphones
- 2 - Shock Mount
- 3 - Power 220V AC
- 4 - RJ43
- 5 - USB
- 6 - Clock & Timer
- 7 - Heigh Adjustment
- 8 - PC On/Off
- 9 - 22" Multi Touch Screen
- 10 - Creapen Annotation Software

CONNECTIVITY OUT



MODEL	TW23P	TW23P
Front Panel	32"	-
Resolution	1920x1080 FHD	-
Brightness	350 cd/m2	-
Aspect Ratio	16:9	-
Panel Type	IPS	-
Front Panel Player	Digital Signage Media Player	-
Lecturer Panel	22"	22"
Screen		
Resolution	1920x1080	1920x1080
Brightness	250 cd/m2	250 cd/m2
Aspect Ratio	16:9	16:9
Number of Touch Point	10 Points Capacitive	10 Points Capacitive
Lecturer Panel PC		
CPU	Intel i3	Intel i3
RAM	4 GB DDR4	4 GB DDR4
HDD	120 GB SSDE	120 GB SSDE
Operation System	Windows 10 Pro	Windows 10 Pro
Microphone		
Lenght	18"	18"
No of Microphone	2 pcs	2 pcs
Output Connector	3-way XLR(Male)	3-way XLR(Male)
Microphone Type	Cardioid	Cardioid
Frequency Response	50 - 18 kHz	50 - 18 kHz
Power ON Indicator	LED	LED
Power Requirement	Phantom Power (48V)	Phantom Power (48V)
Outputs (Bottom of Podium)		
HDMI	Available (Projector Out)	Available (Projector Out)
Ethernet	Network Connection	Network Connection
XLR for Microphone	3-way XLR(Male)	3-way XLR(Male)
USB	USB 2.0 (for internal PC)	USB 2.0 (for internal PC)
Electrical Lifting Column for Height Adjustment		
Movement	Vertical (Up/Down)	
Control	By Buttons (Up/Down) and Remote Control	
Speed	Max speed: 38 mm/s	
Lifting Strength	700N	
Locking System	Automatic Locking when engine not working	
Engine Type	Electrical	
Mechanical Specs		
Outline Dimesion(mm)Set	689 x 850 x 1159	689 x 850 x 1159
Outlibe Dimension(mm)Package	820 x 990 x 1390	820 x 990 x 1390
Weight(kg)	Set: 73 kg Package: 129 kg	Set: 73 kg Package: 129 kg