

# ML22T PRO

ML22T Pro covers your professional presentation requirements and complex needs with its complete solutions. Sliding top panel both protects your touch display and becomes a platform for your documents, laptop.

Multi-purpose complete connector panels give ability to access to power, external protector and display devices, Speakers can convey their voice through meetings rooms, and lecture halls It is equipped with personal computer with the ML22T Pro which has a wide body large enough to be able to harbor all types of sound and imaging devices and a front and back services cover, you can gather all your conference devices into one place without needing an external space



	ML22T PRO
Multi touch speaker screen	22"
Player PC : Intel i3 4GB, I20 SSD, Windows 10 Pro	•
Switcher & Scalar (HDMI & VGA in)	•
Microphone	•
Creapen Annotation Software	•
3.5" Digital Touch Timer	•
7" Controller Tablet	•
Amplifier	Optional
Speakers	Optional

# ML22T PRO

## CONNECTIVITY IN



- 1 - Power 220V AC
- 2 - RJ45
- 3 - VGA
- 4 - HDMI
- 5 - USB 3.0
- 6 - Clock & Timer
- 7 - PC On/Off
- 8 - 22" Multi Touch Screen
- 9 - Shock Mount
- 10 - Mouse Drawer
- 11 - Projection Control
- 12 - 18" Microphones
- 13 - Creapen Annotation Software
- 14 - Sliding top platform

## CONNECTIVITY OUT



MODEL	ML22T PRO
<b>Lecturer Panel</b>	22"
<b>Screen</b>	
Resolution	1920x1080
Brightness	250 cd/m2
Aspect Ratio	16:9
Number of Touch Point	10 Points Capacitive
<b>Lecturer Panel PC</b>	
CPU	Intel i3
RAM	4 GB DDR4
HDD	120 GB SSDE
Operation System	Windows 10 Pro

<b>Tablet Controller</b>	
Layout size	181mm(L)x109mm(W)x9.3mm(H)
Active Area (A.A)	164.90mm(L)x100.00mm(W)
Visual Area (V.A)	154.08-mm(L)x85.92mm(W)
Resolution	800x480 pixel also can be set as 480x800
Touch Type	Capacitive
Touches	1 million
Backlight	LED
Brightness	300nit 0% to 100%

<b>Microphone</b>	
Lenght	18"
No of Microphone	1 pcs
Output Connector	3-way XLR(Male)
Microphone Type	Cardioid
Frequency Response	50 - 18 kHz
Power ON Indicator	LED
Power Requirement	Phantom Power (48V)

<b>Outputs (Bottom of Podium)</b>	
HDMI	Available (Projector Out)
Ethernet	Network Connection
XLR for Microphone	3-way XLR(Male)
USB	USB 2.0 (for internal PC)

<b>Mechanical Specs</b>	
Outline Dimesion(mm)Set	754 x 810 x 1049
Outlibe Dimension(mm)Package	890 x 906 x 1255
Weight(kg)	Set: 104 kg Package: 161 kg