



DS SERIES

DS431LT4


43" 2,500 nits High Brightness
Digital Signage Display



SUNLIGHT
VIEWABLE IMAGE




NARROW
BEZEL



BUILT-IN
MEDIA PLAYER



TRUECOLOR™
CALIBRATED



24 / 7
OPERATION

Android is a trademark of Google LLC.
The Android robot is reproduced or modified from work created and shared by Google and used according to terms
described in the Creative Commons 3.0 Attribution License.

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan



SPECIFICATION

MODEL	DS431LT4	
PANEL	LCD Panel Size	42.5"
	Native Resolution	1920 x 1080
	Backlight	LED
	Default Color Temperature	User 2
	Brightness	2500 nits
	Color Depth	8 bits
	Contrast Ratio	4000:1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
Blackening Defect Free	Up to 110°C (230°F)	
POWER	Power Supply	Internal
	Rated Voltage	100-240V ~ 50/60HZ
	Power Consumption (Typ./ Max.)	180 W / 275 W [TBC]
	Power Saving Mode	< 0.5 W
MECHANICAL SPECS	Bezel Width (T/B/L/R)	8.7 / 8.7 / 8.7 / 8.7 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD)	962.1 x 552.0 x 77.4 mm
	Monitor Weight	18.1 kg [TBC]
	Orientation	Portrait / Landscape
	VESA Mounting (LxH)	400 x 200 mm
	Carrying Handles	Yes
FEATURE	Language	English
	Support SNMP (Up to V3.0)	Yes
	Image Retention Protection	Yes
	Auto Orientation Sensor	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
OSD Menu Rotation	Yes	
INPUT	HDMI 2.1d (HDCP 2.2)	x2 (1080p recommended)
	USB 2.0	x2
OUTPUT	Audio	x1
EXTERNAL CONTROL	RS-232	x1
	RJ-45	x1 (LAN)
INTERNAL PLAYER	Operating System	Android 11.0
	Processor	Quad-core A53
	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2GB
	Graphics	Mali G52
	Storage	Internal: 8GB eMMC Flash
	Multimedia	4K video decoders, 30/60fps H.265 /VP9 10bit, MPEG-1/2/4
Wi-Fi Specification	802.11a/b/g/n/ac (2T2R) 2400.0MHz - 2483.5MHz	
ENVIRONMENT	Operating Temperature	0° ~ 45° C
	Storage Temperature	-20° ~ 60° C
	Humidity	10% ~ 80% RH Non-condensing
CERTIFICATION	CE / FCC / RoHS / CB / UL	

DIMENSIONS

PRELIMINARY

Unit: mm [inch]



INTERFACE

