

DW551DR4

USER MANUAL

55" Dual Side Digital Signage Display

Please read this manual carefully before operating the product and keep it for future reference. The use of diagrams and illustrations in the manual are for reference only, the actual product may differ.



FOR MORE INFORMATION

For more information about DynaScan, visit our site at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan

66501 | V2.02

Contents

Material Contents Declaration	2
Recycling and Energy Information	2
Declaration of Conformity	3
Déclaration de conformité.....	4
Safety Precautions	5
Précautions relatives à la sécurité.....	6
Important Safety Information	7
Informations importantes relatives à la sécurité	8
Getting Started	9
Contents	9
Installing and Replacing Remote Control Batteries.....	9
Bien débuter	10
Contenu	10
Mise en place et remplacement des piles de la télécommande.....	10
Installation.....	11
Connecting to a Power Source.....	14
Connecting an External Video Source	14
Input / Output Terminals	15
Operating Instructions	15
Powering On/Off the Display	16
Using the Remote Control	17
Navigating the On Screen Display (OSD) Menu	19
Specifications	25
Input Mode.....	26
Pin Assignments.....	27
RS-232 Input	27
Troubleshooting.....	28
About DSM365	29

Material Contents Declaration

Part Name	Hazardous Substances					
	Lead	Mercury	Cadmium	Hexavalent Chromium	Polybrominated Biphenyls	Polybromodiphenyl Ethers
Pb	Hg	Cd	Cr ⁶⁺	PBB	PBDE	
PCBA	O	O	O	O	O	O
CHASSIS	O	O	O	O	O	O
ACCESSORY	O	O	O	O	O	O
PACKAGE	O	O	O	O	O	O

“O” indicates that the level of the specified chemical substance is less than the threshold level specified in the standards of SJ/T-11363-2006 and EU 2011/65/EC.
“X” indicates that the level of the specified chemical substance exceeds the threshold level specified in the standards of SJ/T-11363-2006 and EU 2011/65/EC.

Recycling and Energy Information

DynaScan is firmly committed to its environmental protection efforts and we believe that reducing our products' impact on the environment is of the utmost importance. We are dedicated to meet the latest environmental protection regulations.

Energy usage

Mode	Energy Consumption
Normal	Max. 380W
Standby	< 1W

Disposal

Do not dispose of electrical appliances as unsorted municipal waste, use separate collection facilities. Contact your local government for information regarding the collection systems available. If electrical appliances are disposed of in landfills or dumps, hazardous substances can leak into the groundwater and get into the food chain, damaging your health and well-being. When replacing old appliances with new one, the retailer is legally obligated to take back your old appliances for disposal at least for free of charge.



Declaration of Conformity

FCC

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FEDERAL COMMUNICATIONS COMMISSION INTERFERENCE STATEMENT

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

CAUTION:

Any changes or modifications not expressly approved by the grantee of this device could void the user's authority to operate the equipment.

Manufacturer Name DynaScan Technology Corp.

Manufacturer Address 7F, 66 Huaya 1st Road, Guishan, Taoyuan 33383,Taiwan



This device complies with **Directive 2014/53/EU** issued by the Commission of the European Community.

Article (a) EN 62368-1:2014/AC:2015 IEC 62368-1	Article (b) EN 55032:2015/AC:2016 Class A EN 61000-3-2:2014 EN 61000-3-3:2013 EN 55035:2017
---	---

Déclaration de conformité

FCC

Cet appareil est conforme à la section 15 de la réglementation FCC. Son utilisation est sujette aux deux conditions suivantes : (1) cet appareil ne doit pas causer d'interférence nuisible, et (2) cet appareil doit accepter toute interférence reçue, y compris celles qui peuvent causer un fonctionnement non souhaité.

DÉCLARATION DE LA COMMISSION FÉDÉRALE DES COMMUNICATIONS

Cet équipement a été testé et déclaré conforme aux limites d'un appareil numérique de classe A, conformément à la partie 15 des règles FCC. Ces limites sont conçues pour fournir une protection raisonnable contre les interférences nuisibles lorsque l'équipement est utilisé dans un environnement commercial. Ce l'équipement génère, utilise et peut émettre de l'énergie radiofréquence et, s'il n'est pas installé et utilisé conformément au manuel d'instructions, peut provoquer des interférences nuisibles aux communications radio.

Le fonctionnement de cet équipement dans une zone résidentielle est susceptible de provoquer des interférences nuisibles, auquel cas l'utilisateur devra corriger les interférences à ses propres frais.

ATTENTION :

Tout changement ou modification, non expressément approuvé par le responsable de la conformité, peut révoquer l'autorité de l'utilisateur à employer l'appareil en question.

Nom du fabricant DynaScan Technology Corp.

Adresse du fabricant 7F, 66 Huaya 1st Road, Guishan, Taoyuan 33383, Taïwan



Cet appareil est conforme à la **directive 2014/53/UE** émise par la Commission de la Communauté européenne.

L'article (a) EN 62368-1:2014/AC:2015 IEC 62368-1	L'article (b) EN 55032:2015/AC:2016 Classe A EN 61000-3-2:2014 EN 61000-3-3:2013 EN 55035:2017
---	--

Safety Precautions

CAUTION	
	<p>Do not install near flammable material or any heat sources.</p> <p>Do not defeat the safety purpose of the grounding-type plug.</p> <p>Do not disassemble the display to avoid electrical shock or burn.</p> <p>Normal operating condition considers installation at an altitude below 2000m; some abnormalities may be experienced when installed at an altitude above 2000m.</p>
WARNING	
	<p>Please power off the LCD and the video source before plugging in the DP or HDMI cable.</p> <p>Please installed the display in well-ventilated place, do not install in a confined space.</p> <p>Suitable for mounting on concrete or other non-combustible surface only.</p> <p>If it gives off smoke, strange smell, or unusual noise, or when it gets too hot to touch, immediately unplug the display and contact the dealer.</p> <p>Clean only with soft, dry cloth but not use chemical liquids, and unplug while cleaning.</p> <p>Do not use extreme force or any sharp or pointed objects to touch the display.</p> <p>Do not drop or allow any object to fall to the display.</p> <p>Do not operate the display with wet hands to avoid electric shock.</p> <p>Do not discard this product with general household waste. Please be sure to comply with the local waste regulations.</p> <p>This device uses, generates and radiated radio frequency energy. The radio frequency energy produced by this device is well below the maximum exposure allows by Federal Communications Commission (FCC).</p> <p>When a stationary or fixed image is displayed on the screen for a long time, the image may be permanently imprinted on the screen. This phenomenon is known as image burn-in and is not covered by the manufacturer's warranty.</p> <p>In order to avoid burn-in, avoid prolonged display of static or fixed images on the screen.</p> <p>Power supply cord must not be attached to the building surface, nor run through walls, ceilings, floors and similar openings in the building structure.</p> <p>Power cord shall be connected to a socket-outlet with earthing connection.</p>

Précautions relatives à la sécurité

PRÉCAUTIONS	
	<p>N'installez pas installer à proximité de matériaux inflammables ou de sources de chaleur.</p> <p>Ne pas compromettre la sécurité de la fiche de mise à la terre.</p> <p>Pour éviter tout choc électrique ou la brûlure, ne démontez pas l'écran.</p> <p>Le produit peut normalement être utilisé à une altitude inférieure à 2000 m. Des anomalies peuvent survenir lors de l'installation de l'appareil à une altitude supérieure à 2000 m.</p>

AVERTISSEMENT	
	<p>Veuillez éteindre l'écran LCD et la source vidéo avant de brancher le câble DP ou HDMI.</p> <p>Veuillez installer l'écran dans un endroit bien ventilé, pas dans un espace confiné.</p> <p>Convient pour le montage sur du béton ou autre surface non combustible uniquement.</p> <p>S'il dégage de la fumée, une odeur étrange ou un bruit inhabituel, ou s'il est trop chaud au toucher, débranchez immédiatement l'écran et contactez le revendeur.</p> <p>Nettoyez uniquement avec un chiffon doux et sec, sans utiliser de produits chimiques, et débranchez-le pendant le nettoyage.</p> <p>N'exercez pas une force excessive et n'utilisez pas d'objets tranchants ou pointus pour toucher l'écran.</p> <p>Ne laissez pas tomber l'écran et ne laissez aucun objet tomber dessus.</p> <p>Afin d'éviter tout choc électrique, n'utilisez pas l'écran avec les mains mouillées.</p> <p>Ne jetez pas ce produit avec les déchets ménagers. Assurez-vous de respecter les réglementations locales en matière de déchets.</p> <p>Cet appareil utilise, génère et rayonne de l'énergie radiofréquence. L'énergie de radiofréquence produite par cet appareil est bien inférieure à l'exposition maximale autorisée par la FCC (Federal Communications Commission).</p> <p>Lorsqu'une image immobile ou fixe est affichée sur l'écran pendant une longue période, l'image peut être imprimée de manière permanente sur l'écran. Ce phénomène est connu sous le nom d'image rémanente et n'est pas couvert par la garantie du fabricant.</p> <p>Afin d'éviter toute détérioration, évitez l'affichage prolongé d'images statiques ou fixes sur l'écran.</p> <p>Le cordon d'alimentation ne doit pas être connecté à la surface du bâtiment, ni traverser les murs, les plafonds, les planchers et les ouvertures similaires du bâtiment.</p> <p>Le cordon d'alimentation doit être connecté à une prise électrique mise à la terre</p>

Important Safety Information

- Disassembling the LCD is strictly prohibited. Opening the cover may expose the user to electric shock or other hazards. Please contact DynaScan certified service professionals for all maintenance requirements.
- Do not allow any liquid to enter the LCD. Also avoid placing the LCD close to water sources.
- Do not place heavy objects on the power cord. A damaged power cord might cause electric shock or fire.
- Do not bend, twist, or damage the power cord.
- The power cord must comply with the local safety regulations.
- Do not damage or modify the prongs/pins and the ground contact on the power cord plug.
- Do not place the LCD on an unleveled surface or an unstable vehicle. The LCD could fall over and cause substantial damage.
- Do not cover the vents and/or the heat sink.
- Do not install the LCD beside radiators or other heat sources. The installation site should have sufficient ventilation so the heat generated by the LCD can be dissipated.
- Do not use the Signage in a hot, humid, dusty, or fumy environment.
- Handle the LCD with care. Save the packaging materials for transport later.
- Clean the LCD backside at least once a month for dust and other particles.

Unplug the LCD immediately and contact a DynaScan certified service professional as soon as possible when any of the following situations occurs:

- Damaged power cord or power plug.
- If liquid or foreign object has entered the LCD.
- If the LCD has been exposed to rain or water.
- If the LCD has been dropped or the casing has become damaged.
- If any structural damage such as cracks or unnatural vibration is found.
- If the LCD cannot be operated following the steps outlined in this manual.
- If the LCD emits smoke or other odors, or generates strange noises.

Operating Suggestions

- Avoid displaying a stationary image for a long period of time in order to prevent image sticking.

Cleaning the Panel

- Use a soft, lint-free cloth to gently wipe the dust off from the screen panel.
- Do not use any hard material to wipe the panel.
- Do not poke the panel with your hand or any sharp object (such as a pen or a nail) or exert excessive pressure on the panel to prevent any damage.
- Do not use any cleaning solutions on the panel as it might cause discoloration.

Cleaning the Casing

- Unplug the power cord.
- Gently wipe the casing with a soft cloth.

Attention

- Do not use any of the following solutions to clean the casing as they may damage the paint and cause it to crack or peel: benzene solution, alkaline solution, alcohol-based cleaning solution, glass cleaner, wax, polisher, or detergent.

Informations importantes relatives à la sécurité

- Le démontage de l'écran LCD est strictement interdit. L'ouverture du capot peut exposer l'utilisateur à un choc électrique ou à d'autres dangers. Veuillez contacter des professionnels de service certifiés DynaScan pour tous les besoins de maintenance.
- Ne laissez aucun liquide pénétrer dans l'écran LCD. Évitez également de placer l'écran LCD à proximité de sources d'eau.
- Ne placez aucun objet lourd sur le cordon d'alimentation. Un cordon d'alimentation endommagé peut provoquer un choc électrique ou un incendie.
- Ne pliez pas, ne tordez pas et n'endommagez pas le cordon d'alimentation.
- Le cordon d'alimentation doit être conforme aux réglementations locales de sécurité.
- Veillez à ne pas endommager ni modifier les broches ou le contact de terre sur la fiche du cordon d'alimentation.
- Ne placez pas l'écran LCD sur une surface qui n'est pas de niveau ou sur un véhicule instable. L'écran LCD pourrait tomber et causer des dégâts importants.
- Ne couvrez pas les orifices de ventilation et / ou le dissipateur de chaleur.
- N'installez pas l'écran LCD à côté de radiateurs ou d'autres sources de chaleur. Le site d'installation doit disposer d'une ventilation suffisante pour que la chaleur générée par l'écran LCD puisse être dissipée.
- N'utilisez pas l'affichage signalétique dans un environnement chaud, humide, poussiéreux ou enfumé.
- Manipulez l'écran LCD avec soin. Conservez les matériaux d'emballage pour tout transport ultérieur.
- Nettoyez l'arrière de l'écran LCD au moins une fois par mois afin d'éliminer la poussière et autres particules.

Débranchez immédiatement l'écran LCD et contactez un réparateur professionnel certifié DynaScan dès que possible lorsque l'une des situations suivantes se produit :

- Cordon d'alimentation ou fiche d'alimentation endommagé.
- Si du liquide ou un corps étranger est entré dans l'écran LCD.
- Si l'écran LCD a été exposé à la pluie ou à l'eau.
- Si l'écran LCD est tombé ou si le boîtier a été endommagé.
- Si vous constatez des dommages structurels comme des fissures ou des vibrations non naturelles.
- Si l'écran LCD ne peut pas être utilisé en suivant les étapes décrites dans le présent manuel.
- Si l'écran LCD émet de la fumée ou d'autres odeurs, ou génère des bruits étranges.

Suggestions d'utilisation

- Évitez d'afficher une image immobile pendant une période prolongée afin d'éviter que la rémanence d'image.

Nettoyage du panneau

- Utilisez un chiffon doux non pelucheux pour essuyer délicatement la poussière du panneau de l'écran.
- N'utilisez aucun matériau dur pour essuyer le panneau.
- Afin d'éviter tout dommage, n'appuyez pas sur le panneau avec votre main ou un objet pointu (comme un stylo ou un ongle) et n'exercez pas de pression excessive sur le panneau.
- N'utilisez aucune solution de nettoyage sur le panneau car cela pourrait provoquer une décoloration.

«Danger de stabilité» ou libellé équivalent;

«Le moniteur peut tomber, entraînant des blessures graves ou mortelles» ou texte équivalent;

Le texte suivant ou équivalent:

Pour éviter les blessures, ce moniteur doit être solidement fixé au sol / mur conformément aux instructions d'installation.





Getting Started

Contents

Confirm that the accessories below are shipped along with the display. If any item is missing, please contact your dealer. The color and shape of the accessories may vary with the products.

- DW551DR4 Professional LCD.
- Remote Control x 1 pc.
- Batteries (1.5V / AAA) x2 pcs.
- Power cable x1 pc.
- Quick Start Guide x1 pc.
- ESK302 x2 pcs.

Attention: Please use the following table to check whether the included power cord is suitable for your region. If the power cord does not match your region, please contact your local supplier. Please use matching AC socket in order to meet your local safety regulations.

Plug Type	North America	European Continental	Japan	Taiwan
Plug Shape				
Region	U.S.A. / Canada	EU (Except U.K.)	Japan	Taiwan
Voltage	120V	230V	100V	110V
NEMA TYPE	NEMA 5-15	CEE 7/7	NEMA 1-15	NEMA 5-15
IEC Display Plug				
IEC Plug TYPE	IEC320 C13			

Installing and Replacing Remote Control Batteries

1. Open the battery compartment cover.
2. Insert 2 new AAA batteries.
3. Close the battery compartment cover.

Warning:

- Incorrect usage of batteries may cause leakage or explosion.
- Pay attention to the polarity when installing the batteries.
- Do not mix different types of batteries or new and used batteries. Doing so may shorten the battery life or cause leakage.
- Remove or replace the batteries when they are empty in order to prevent acid leaking in the battery compartment.
- Do not touch the leaked substance from the batteries in case of a battery leakage. Doing so may hurt human skin.

Note: If the remote control is not going to be used for a long time, we recommend removing the batteries from the remote control.

Bien débuter

Contenu

Vérifiez que les accessoires ci-dessous sont fournis avec l'écran. Si l'un d'eux est manquant, veuillez contacter immédiatement votre revendeur. La couleur et la forme des accessoires peuvent varier selon les produits.

- Écran LCD DW651LR5 Professional.
- Télécommande x 1
- Piles (1,5V / AAA) x 2
- Câble d'alimentation x 1
- Guide de démarrage rapide x 1
- ESK302 x 2

Attention : Veuillez utiliser le tableau suivant afin de vérifier que le cordon d'alimentation fourni est adapté à votre région. Si le cordon d'alimentation ne correspond pas à votre région, veuillez contacter votre fournisseur local. Veuillez utiliser la prise secteur correspondante afin de respecter les réglementations locales de sécurité.

Type de fiche	Amérique du Nord	Europe continentale	Japon	Taiwan
Forme de la fiche				
Région	États-Unis / Canada	UE (Hors R.-U.)	Japon	Taiwan
Tension	120V	230V	100V	110V
TYPE NEMA	NEMA 5-15	CEE 7/7	NEMA 1-15	NEMA 5-15
Fiche d'affichage CEI				
TYPE fiche CEI			IEC320 C13	

Mise en place et remplacement des piles de la télécommande

1. Ouvrez le couvercle du logement à piles.
2. Insérez 2 nouvelles piles AAA.
3. Fermez le couvercle du logement à piles.

Avertissement :

- Une mauvaise utilisation des piles peut provoquer des fuites ou une explosion.
- Faites attention à la polarité lors de l'installation des piles.
- Ne mélangez pas différents types de piles ou des piles neuves et usagées. Cela pourrait raccourcir la durée de vie des piles ou causer des fuites.
- Retirez ou remplacez les piles lorsqu'elles sont vides afin d'éviter toute fuite d'acide dans le logement à piles.
- Ne touchez pas la substance qui s'écoule des piles en cas de fuite. Cela pourrait blesser la peau.



Remarque : Si la télécommande ne doit pas être utilisée pendant une période prolongée, nous vous recommandons d'en retirer les piles.

Installation

The LCD has been designed with two ways installation, which suitable for (1) Stand and (2) Ceiling Mount applications. Please note that the display must be properly installed onto the stand (DynaScan optional kit) or well-connected with the hanging kit (DynaScan optional kit), details please refer to the display installation guide. Incorrect installation may cause injury or damage the equipment. Product warranty does not cover the damage caused by improper installation and DynaScan shall not be held responsible in such incident. If you attempt to install the LCD on a different way, such as hanging from the ceiling with your customized hanging kit or your own platform/ enclosure; please contact DynaScan directly for more assistance. Please follow the local regulations for safety handling and display installation, this equipment is intended to be installed by qualified service personnel.

(1) Stand


Model	Screw Location		Screw Specification	Screw Length	Number
DW551DR4	A	31.3 * 1088.9 31.3 * 1148.9 31.3 * 1208.9	M6	7mm is required	12
	B	31.3 * 63.9 31.3 * 123.9 31.3 * 183.9			




1. Two mounting holes can be found from top and bottom sides of the display (Portrait mode), which are reserved for wall, ceiling or stand mounting use.
2. When the connection kit insert into the mounting hole, each length side of the display has six screw holes which can be used for fasten.

Orientation

- DW551DR4 provides 3 different screen orientations for various environment applications. Portrait Flip, Portrait and Landscape mode can be distinguished by the corresponding position of I/O port in the figures below.



Mode 1 : Portrait Flip




Mode 2 : Portrait



Mode 3 : Landscape

Installation Location

- Do not install in a location with strong vibrations or dusty.
- Do not install near the building's main electric panel.
- Ensure the LCD is secured in such a manner that it cannot be easily removed by the general public.
- Leave clearance around the outer edge of the LCD from other objects to ensure proper ventilation.



Maintenance


- Inspect the fasteners regularly for signs of loosening or deformation. Please perform appropriate corrective measures when a problem is identified. Neglecting the problem may worsen the situation.
- Increase the inspection frequency on areas where previous maintenance had occurred to ensure the problems do not occur again.

Connecting to a Power Source

Using the power cable provided, plug it in the power inlet which shown in the diagram below. Connect the power cable to a 100-240 volt, 50 / 60Hz AC power outlet.






Insert the plug completely into the socket. A loose power connection may cause damage to the display and/or lead to a fire hazard.




Connecting an External Video Source

Turn OFF the power of both LCD and external video device. Using the DP cable (or HDMI cable, DVI cable), insert one end into the DP-IN (or HDMI-IN, DVI-IN) which shown in the diagram below. Connect the other end of the DP cable (or HDMI cable, DVI cable) to the DP output (or HDMI output, DVI output) of the video source. Refer to your video device's manual for additional information.



Input / Output Terminals


- A. **RS-232 (IN):** RS232C network input connection for remote control from PC.
- B. **DVI (IN):** Connect the DVI-D output of a PC, or the HDMI output of an AV device via a DVI-HDMI cable.
- C. **HDMI (IN):** Connect the HDMI output of a PC or an AV device via a HDMI cable.
- D. **DP (IN):** Connect the DP output of a PC or an AV device via a DP cable.
- E. **Extension Connector:** Extension Connector for optional IR Extension sensor kit (ESK302).
- F. **Thermal:** Extension Connector for optional Extension thermal kit (ETK302).
- G. **Audio (OUT):** Connect the audio signal output from Audio IN jack to an external AV device.
- H. **AC (IN):** Connect the supplied power cord to the wall outlet.
- I. **Power Switch:** Press to switch the main power on/off.
- J. **Reset:** Press to reboot the internal player.
- K. **RJ-45 (IN):** RJ45 network input connection.
- L. **Micro SD card:** Support for up to 32GB.
- M. **USB port:** Support for USB flash drive storage, mouse and keyboard.



Operating Instructions

Powering On/Off the Display

To turn on/off the display. Press the power switch on as shown in the diagram below.




NOTE: The remote control only works when the power switch is ON.


Using the Remote Control

Connection using an External Sensor Kit (ESK302)

Connect the ESK302 cable to the mini USB port, and aim the remote at the IR receiver as shown below.



NOTE: Ambient light may affect the performance of the remote control. Avoid fluorescent or neon lights in the vicinity.



*Color and shape may vary by model.

ITEM		DESCRIPTION
①	POWER	Power On / Off
②	MENU	OSD On / Off
③	UP	Move the cursor up or change the setting of selected item.
④	LEFT	Exit the current selection.
⑤	RIGHT	Select the highlighted item.
⑥	DOWN	Move the cursor down or change the setting of selected item.
⑦	OK	Enter (for DSM365 only)
⑧	BACK	Return to the last page. (for DSM365 only)

Navigating the On Screen Display (OSD) Menu

Press the MENU button on the remote control to show the OSD. Use the navigation arrows to select and adjust the menu items.

*The change of each setting can only enable when you press "LEFT" (refer to p.18) to back to the last menu layer.

1. Input Source

Input Source	Main Failover 1 Failover 2 Failover 3	HDMI DP DVI DSM365
Picture		
Time		
Backlight		
Advance		

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Input Source	Main	HDMI	Set the Main input to display.
	Failover 1	DP	Set the Failover 1 input to display.
	Failover 2	DVI	Set the Failover 2 input to display.
	Failover 3	DSM365	Set the Failover 3 input to display.

2. Picture

Input Source	Color Temperature R G B Contrast Gamma Sharpness Black Level	User 2 100 100 100 50 2.2 Low RGB Full
Picture		
Time		
Backlight		
Advance		

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Picture	Color Temperature	USER 2	Select the color temperature. (User2, User1, D93, D65 and D55).
	Red		Adjust the red light level. Range 0 – 100. Note: The feature is only supported on User2 mode.
	Green		Adjust the green light level. Range 0 – 100. Note: The feature is only supported on User2 mode.
	Blue		Adjust the blue light level. Range 0 – 100. Note: The feature is only supported on User2 mode.
	Contrast	50	Adjust the contrast level. Range 0 – 100.
	Gamma	2.2	Adjusts the Gamma value. (Native, 2.2, 2.4 and sGamma)
	Sharpness	Low	Adjusts the Sharpness value. (High, Medium and Low)

	Black Level	RGB Full	Selects the black level to adjust the screen gray scale. "Limited" for video source uses 16 to 235 levels for R/G/B, such as HDMI. "RGB Full" for video source uses all levels from 0 to 255 levels.
--	-------------	----------	--

3. Time

Input Source	Current Date	2020/06/09
Picture	Current Time	05:19:30
Time	Day of Week	Tuesday
Backlight	Daylight Saving	Off
Advance	Power Control Timer	Off
	Power On Time	00:00
	Power Off Time	00:00

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Time	Current Date	YYYY:MM:DD	Set the date.
	Current Time	HH:MM:SS	Set the clock. Note: The internal clock will continue to function when the power is turned off.
	Day of Week		Set the day of week. (Monday to Sunday)
	Daylight Saving	Off	Turn on / off DST setting.
	Power Control Timer	Off	Automatic power on / off schedule function.
	Power On Time	00:00	Set turn-on time.
	Power Off Time	00:00	Set turn-off time.

4. Backlight

Input Source	Auto Brightness	Off
Picture	High Level	100
Time	Low Level	30
Backlight	High Level Time	00:00
Advance	Low Level Time	00:00
	Local Dimming	Medium
	ALS Threshold	01(88)

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Backlight	Auto Brightness	Off	<p>A. If the AUTO BRIGHTNESS is "Off", the screen brightness will remain at HIGH LEVEL brightness value.</p> <p>B. If the AUTO BRIGHTNESS is "Auto", the brightness of display will be adjusted according to the ambient light. When ambient light is bright, the screen will adjust to the High Level brightness value set; when ambient light is dark, the screen will adjust to the Low Level brightness value set.</p> <p>C. When the Timer ("High Level Time" & "Low Level Time") mode is set, the display will automatically switch the brightness according to the time set.</p>
	High Level	100	Adjusts the highest brightness level. Range 0 – 100.
	Low Level	30 (1000 nit) 10 (3000 nit)	Adjusts the lowest brightness level. Range 0 – 100.
	High Level Time	00:00	Set high level time.
	Low Level Time	00:00	Set low level time.
	Local Dimming	Medium	Adjusts the contrast. High is the highest contrast. Off is the lowest contrast. (Off, Low, Medium and High)
	ALS Threshold		<p>Set the switching threshold value of High Level and Low Level. This function only supports the AUTO BRIGHTNESS is "Auto".</p> <p>Note: If the ambient light is below the threshold value, the display will be switched to Low Level mode. If the ambient light is above the threshold value, the display will be switched to High Level mode.</p>

5. Advance

Input Source	Display Mode	Auto
Picture	Screen Protection	Off
Time	IR Control	On
Backlight	Power Off Mode	Standby
Advance	Volume	100
	AC Back Status	Power On
	Reset to Default Setting	Off

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Advance	Display Mode	Auto	Change the Menu orientation. The Menu can be displayed in either LANDSCAPE, PORTRAIT or PORTRAIT FLIP mode.
	Screen Protection	Off	Turn on / off image burn-in protection. Set image burn-in protection interval. Range 0 – 100 minutes.
	IR Control	On	Enable/disable the remote control for Menu. Note: When disabled, the remote control function can be enabled again from the control panel on the display or through the DynaScan "Display Manager" application.
	Power Off Mode	Standby	When in Power Off Mode, RS-232 controls do not function. Only [Main Power Switch] on the display or [Power Button] on the remote control can wake up the display.
	Volume	100	Set volume. Range 100 – 0.
	AC Back Status	Power On	Choose to use the AC back status function. <u>Power On</u> : Display booting up when the power back after an outage. <u>Standby</u> : Display keeps soft-off status when the power back after an outage. <u>Memory</u> : Display will back to the last state when the power back after an outage.
	Reset Default Setting	Off	Restore all settings to default. Note: It does not modify CURRENT DATE, CURRENT TIME, DATE OF WEEK, TIME ZONE, POWER ON TIME and POWER OFF TIME.

6. Information 1

Information 1	Resolution	HDMI 1920x1080
Information 2	Model	DW551DR4
Information 3	Serial Number	551DR4XXXXXXX
	Hardware	XXXX
	Firmware	XX.XX.X
	Color Depth	8 bits

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Information 1	Resolution		Input resolution.
	Model	DW551DR4	The display's model.
	Serial Number		The display's serial number.
	Hardware		The H/W version.
	Firmware		The F/W version.
	Color Depth		The color depth of current input.

7. Information 2

Information 1	Amb. Temp. (Back)	27°C/ 80°F
Information 2	Amp. Temp. (ETK)	No Connection
Information 3	ALS Level (Amb.)	10

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Information 2	Amb. Temp. (Back)		LCD inner (backlight unit) temperature monitoring.
	Amb. Temp. (ETK)		The Extension Thermal Kit (ETK302) is for ambient temperature monitoring.
	ALS Level		The brightness of ambience monitoring. (Ambience Light Sensor)

8. Information 3

Information 1	Over Heat Protection	Inactive
Information 2		
Information 3		

ITEM 1	ITEM 2	DEFAULT	DESCRIPTION
Information 3	Over Heat Protection	Inactive	<p>It will enter into protection mode when the display internal temperature is over heat. 65°C = Brightness 75%. 67°C = Brightness 50%. 69°C = Brightness 10%. When the temperature is decreased to exit the protection, the brightness will restore to 100% and Over Heat Protection is disabled.</p>

Some functions may not be available for all models.



*Adjusted value: Each R/G/B value for this product has been individually adjusted during production to a preset color temperature of 6500K.

Specifications

MODEL	DW551DR4	
PANEL	LCD Panel Size	54.64 inches
	Native Resolution	1920 x 1080
	Brightness	1000 cd/m ² (Typ.) / 3000 cd/m ² (Typ.)
	Contrast Ratio	3,000:1
	Response Time	8 ms (Typ.)
	Viewing Angle	178°/ 178°
	Life Time	100,000 hrs (Typ.)
	Panel Surface	AR 1.5%, 2H
POWER	Power Supply	Internal
	Rated Voltage	100 - 240V, 50 / 60Hz
	Power On Mode	Typ. 240W / Max. 380W
	Power Saving Mode	< 1W
MECHANICAL SPECS	Bezel Width (T/B/L/R)	29.5/29.5/29.5/29.5 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD)	1272.8 x 743.3 x 62.7 mm
	Monitor Weight	43 kg
USER INTERFACE	Orientation	Landscape / Portrait
	OSD Language	English
ENVIRONMENT	Operation Temperature	0°C ~ 45°C
	Storage Temperature	-20°C ~ 60°C
	Humidity	10%~80% RH Non-Condensing
I/O Ports	HDMI	IN *2 (HDCP)
	DP	IN *2
	DVI-D	IN *2
	RS-232	IN *2
	Audio	OUT *2
	USB port	IN *2
	RJ-45	IN *2
	Micro SD Slot	IN *2
	Mini USB	IN *2 (ESK only)
Fuse		6.3A



Design and specifications are subject to change without notice.


Input Mode

Active Resolution		Refresh Rate	Pixel Rate	Aspect Ratio
H Pixels	V Lines			
640	480	60 Hz	25.175 MHz	4:3
720	480	59.94 Hz	27 MHz	4:3
800	600	60 Hz	40 MHz	4:3
1024	768	60 Hz	65 MHz	4:3
1280	720	60 Hz	74.25 MHz	16:9
1280	768	60 Hz	79.5 MHz	5:3
1360	768	60 Hz	85.5 MHz	16:9
1920	1080	60 Hz	148.5 MHz	16:9

Pin Assignments

RS-232 Input

PIN No.	NAME
01	Connected to 7&8
02	TXD
03	RXD
04	Connected to 6
05	GND
06	Connected to 4
07	Connected to 1&8
08	Connected to 1&7
09	NC



Troubleshooting

ISSUE	RECOMMENDED SOLUTION
No image is displayed.	<ul style="list-style-type: none">● Check whether the cable is completely plugged in.● Check whether the main switch is in the ON position, and the power cord is completely plugged in.● Check whether the image source's resolution is set as the supported format (refer to section "Input Mode", p.26).● Check whether the cable is damaged or bent excessively.
Nothing happens when switching the main switch on.	<ul style="list-style-type: none">● Unplug the power cord from the socket and plug it in again after a few seconds to reset the Signage. Note: Unplugging the power cord will not change the settings.
Image is unstable.	<ul style="list-style-type: none">● Check whether the cable is completely plugged in.
The remote control does not work.	<ul style="list-style-type: none">● Check whether there are batteries in the remote control.● Check the batteries for freshness, polarity, etc.● Check whether the remote is in the operation range.● Bright light may interfere with the remote control. Please avoid using the remote control near special fluorescent lights or neon lights.
Auto on/off does not work or does not function properly.	<ul style="list-style-type: none">● Check whether the TIMER setting in the menu is set to "OFF".● Check whether the "Power On Time" and "Power Off Time" settings are set correctly.
Cannot control the display remotely via RS-232.	<ul style="list-style-type: none">● Check whether the RS-232 cable is connected properly.

If you are still having trouble with your DynaScan DS² Professional LCD, contact your dealer or DynaScan directly for more assistance.


About DSM365

DSM365 is an internal operating system as Android, which can install the applications via USB flash drive storage, SD card or Internet.

How to Switch to DSM365

- Press the MENU button on either the rear panel control or remote control to show the OSD.
- Use the navigation arrows to select and adjust the Input Source.
[Input Source → Main → DSM365]

Input Source	Main	DSM365
Picture	Failover 1	DP
Time	Failover 2	DVI
Backlight	Failover 3	HDMI
Advance		



ITEM	DESCRIPTION
① APPS	Show the Installed APPS.

www.dynascandisplay.com