

AVAILABLE FROM CY2022 4Q

Note: release date varies depending on country or region.

# Deliver More for Less with the World's Smallest and Lightest 20,000 lm<sup>1</sup> 3-Chip DLP™ 4K<sup>2</sup> Laser Projector

Note: Based on publicly available dimensions and weight for DLP™ laser projectors with 16,000 lm brightness and above as of January 2022. Release date varies depending on country or region.



[Preliminary Specification] PT-RQ25K Series 3-Chip DLP™ Projectors

	PT-RQ25K	PT-RZ24K	PT-RQ18K	PT-RZ17K
Light Output	20,000 lm <sup>1</sup> / 21,000 lm (Center) <sup>6</sup>		16,000 lm <sup>1</sup> / 16,800 lm (Center) <sup>6</sup>	
Resolution	4K (3840 x 2400 <sup>7</sup> pixels)	WUXGA (1920 x 1200 pixels)	4K (3840 x 2400 <sup>7</sup> pixels)	WUXGA (1920 x 1200 pixels)

Note: Optional 3-Chip DLP™ lenses<sup>8</sup> sold separately. Specifications are tentative.

## • Compact Form-Factor Streamlines Workflow

PT-RQ25K Series is 40 % smaller and 35 % lighter<sup>9</sup> than our 20,000-lm PT-RQ22K with a body size similar to our 10,000-lm 1-Chip DLP™ projectors. Intel® SDM-ready slot integrates your preferred terminals with optional proprietary or third-party<sup>10</sup> function boards. Smart Projector Control<sup>11</sup> app with NFC function<sup>12</sup>, Remote Preview Lite, and preactivated upgrade kits for Geo Pro<sup>13</sup> simplify installation.

## • Create an Engaging Visual Experience

Quad Pixel Drive, our original 2-axis pixel-quadrupling technology, creates smooth 4K<sup>2</sup> images with vivid 3-Chip DLP™ color and high brightness. A new Dynamic Contrast setting delivers higher white brightness and deep blacks during high-contrast scenes. Gradation Smoother reduces color-banding via remote control, while improved point-based black-level adjustment supports edge-blending over curved screens with pixel-level precision.

## • Reliable and Maintenance-free for Peace of Mind

Hermetically sealed optical block is cooled by a high-efficiency liquid-cooling system enabling maintenance-free projection for 20,000 hours<sup>14</sup>. Multi-Laser Drive Engine prevents brightness loss in the event of diode failure, while Backup Input<sup>15</sup> switches to a backup signal if the primary signal is interrupted for peace of mind.

1 Please refer to specifications table for brightness value of individual models. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. 2 PT-RQ25K/RQ18K only with Quad Pixel Drive [ON]. 3 PT-RQ25K/RQ18K only. 4 Only when optional TY-SB01DL DIGITAL LINK Terminal Board (available from CY2022 3Q) is loaded. 5 PT-RZ24K/RZ17K only. 6 Average light-output value of all shipped products measured at center of screen in Normal Mode. 7 Maximum physical resolution with Quad Pixel Drive [ON]. 8 Excluding lenses for the PT-RQ50K projector. 9 Estimated value by cabinet volume and weight (excluding lens) according to Panasonic research. 10 Intel® SDM-specified third-party function boards sold separately. Panasonic cannot guarantee operation of third-party devices. 11 Check device compatibility at the App Store or the Google Play store. 12 Projectors sold in some countries or regions require an ET-NUK10 Upgrade Kit available from PASS to activate NFC function. See NFC Regional Compatibility List for details. 13 Geometry Manager Pro software for Windows® and preactivated upgrade kits require projector registration. Visit PASS to register your projector and download free software. 14 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of airborne particulate matter. Panasonic recommends checkup at point of purchase after about 20,000 hours. Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period. Estimated maintenance time varies depending on environment. 15 Input signals to primary and backup inputs must be identical.

Specifications (Tentative)

Model	PT-RQ25K	PT-RZ24K	PT-RQ18K	PT-RZ17K		
Projector type	3-Chip DLP™ projector					
DLP™ chip	Panel size	20.3 mm (0.8 in) diagonal (16:10 aspect ratio)				
	Display method	DLP™ chip x 3, DLP™ projection system				
	Number of pixels	2,304,000 (1920 x 1200 pixels) x 3				
Light source	Laser diode					
Light output <sup>1,2</sup>	20,000 lm / 21,000 lm (Center) <sup>3</sup>		16,000 lm / 16,800 lm (Center) <sup>3</sup>			
Time until light output declines to 50 % <sup>4</sup>	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)					
Resolution	4K (3840 x 2400 pixels) (Quad Pixel Drive: ON) WUXGA (1920 x 1200 pixels)		4K (3840 x 2400 pixels) (Quad Pixel Drive: ON)	WUXGA (1920 x 1200 pixels)		
Contrast ratio <sup>2</sup>	25,000:1 (Full On/Full Off, Dynamic Contrast [3])					
Screen size (diagonal)	1.78–25.40 m (70–1000 in), 1.78–15.24 m (70–600 in) with ET-D75LE8/ET-D3LET80, 3.05–15.24 m (120–600 in) with ET-D75LE95, 5.08–15.24 m (200–600 in) with ET-D3LEU100/D3LEW200					
Center-to-corner zone ratio <sup>2</sup>	90 %					
Lens	Optional (no lens included with this model)					
Lens shift (From the origin point of the lens mounter)	Vertical	±66 % (±52 % with ET-D75LE6/ET-D3LEW60, +71 % / +93 % with ET-D75LE95, ±66 % with ET-D3LEU100, ±57 % with ET-D3LEW200) (powered)				
	Horizontal	±24 % (±18 % with ET-D75LE6/ET-D3LEW60, ±14 % with ET-D75LE95, -25 % / +30 % with ET-D3LEU100, ±18 % with ET-D3LEW200) (powered)				
Keystone correction range	Vertical: ±45 ° (±40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28 ° with ET-D75LE6/ET-D3LEW60, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW200, ±8 ° with ET-D3LEU100, +5 ° with ET-D75LE95), Horizontal: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5 ° with ET-D3LEU100/ET-D3LEW200, 0 ° with ET-D75LE95) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.					
Installation	Ceiling/floor, front/rear, free 360-degree installation					
Terminals	HDMI IN	HDMI x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input <sup>5</sup> )				
	DisplayPort™	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input <sup>5</sup> ) (TBD)				
	MULTI PROJECTOR SYNC IN	BNC x 1	—	BNC x 1	—	
	MULTI PROJECTOR SYNC OUT	BNC x 1	—	BNC x 1	—	
	MULTI PROJECTOR SYNC IN / 3D SYNC 1 IN/OUT (dual purpose)	—	BNC x 1	—	BNC x 1	
	MULTI PROJECTOR SYNC OUT / 3D SYNC 2 OUT (dual purpose)	—	BNC x 1	—	BNC x 1	
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)				
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)				
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control				
	REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)				
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)				
	LAN	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible				
	USB	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory				
	DC OUT	USB Type A x 1 (for power supply, DC 5 V, 2 A)				
	Expansion slot	Open slot for function boards, Intel® SDM compatible				
	Power supply	AC 100 V–120 V / AC 200 V–240 V, 50 Hz/60 Hz (The maximum value of light output is limited to 15,000 lm or less when using the projector with AC 100 V to AC 120 V. Other limitations apply <sup>6</sup> .)				
Power consumption <sup>7</sup>	Maximum power consumption	1,200 W (1,210 VA) (TBD) / 1,540 W (1,550 VA) (TBD)	1,180 W (1,190 VA) (TBD) / 1,520 W (1,530 VA) (TBD)	1,200 W (1,210 VA) (TBD) / 1,280 W (1,290 VA) (TBD)	1,180 W (1,190 VA) (TBD) / 1,260 W (1,270 VA) (TBD)	
	On-mode power consumption (Operating mode)	[NORMAL]	1,400 W (TBD)	1,380 W (TBD)	1,130 W (TBD)	1,110 W (TBD)
		[ECO]	1,130 W (TBD)	1,110 W (TBD)	940 W (TBD)	920 W (TBD)
		[QUIET]	1,110 W (TBD)	920 W (TBD)	900 W (TBD)	1,090 W (TBD)
Cabinet materials	Molded plastic					
Operation noise <sup>2</sup>	46 dB (NORMAL/ECO) (TBD), 43 dB (QUIET) (TBD)		43 dB (NORMAL/ECO) (TBD), 40 dB (QUIET) (TBD)			
Dimensions (W x H x D)	Approx. 550 x 220 x 570 mm (21 5/8" x 8 11/16" x 22 7/16") (not including protruding parts) (TBD)					
Weight <sup>8</sup>	Approx. 35 kg (77.2 lbs) (TBD)					
Operating environment	Operating temperature: 0–45 °C (32–113 °F) <sup>9</sup> , operating humidity: 10–80 % (no condensation)					
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™					

1 This is the value when the Zoom Lens (Model No.: ET-D3LES20) is used with power supply voltage of AC 200 V to AC 240 V. The value varies depending on the lens. 2 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. 3 Average light-output value of all shipped products measured at center of screen in Normal Mode. 4 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, Normal Mode, Dynamic Contrast [3], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m<sup>3</sup> of particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment. 5 4K signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ24K and PT-RZ17K. 6 Maximum value of light output is further decreased in the following cases: when a function board is installed in the slot, when the light source is deteriorating from use, or when there is dust on the optical parts. 7 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). 8 Average value. May differ depending on the actual unit. 9 When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).

Optional Accessories

- Fisheye Lens** ET-D3LEF70  
Note: Equipped with Auto Lens Identification Function.
- Fixed-Focus Lens**  
ET-D75LE95 (0.437:1) / ET-D3LEU100 (0.447:1) / ET-D3LEW50 (0.838:1)<sup>1</sup>  
<sup>1</sup> Equipped with Auto Lens Identification Function.
- Zoom Lens**  
ET-D3LEW200 (0.779–1.03:1)<sup>1</sup> / ET-D3LEW300 (0.924–1.12:1)<sup>2</sup> / ET-D3LEW60 (1.11–1.32:1)<sup>1</sup> / ET-D75LE6 (1.11–1.32:1) / ET-D3LEW10 (1.52–2.07:1)<sup>1</sup> / ET-D75LE10 (1.56–2.01:1) / ET-D3LES20 (2.00–2.90:1)<sup>1</sup> / ET-D75LE20 (2.00–2.90:1) / ET-D3LET30 (2.88–5.61:1)<sup>1</sup> / ET-D75LE30 (2.89–5.61:1) / ET-D3LET40 (5.54–8.90:1)<sup>1</sup> / ET-D75LE40 (5.55–8.86:1) / ET-D3LET80 (8.83–16.6:1)<sup>1</sup> / ET-D75LE8 (8.83–16.6:1)  
<sup>1</sup> Equipped with Auto Lens Identification Function and Stepping Motor.  
<sup>2</sup> ET-D3LEW300 will be available from CY2023 2Q.
- Ceiling Mount Bracket**  
ET-PKD520H (for high ceilings)  
ET-PKD520S (for low ceilings)  
Note: ET-PKD520H/PKD520S is used in combination with ET-PKD521B (sold separately).
- Attachment for Ceiling Mount Bracket**  
ET-PKD521B  
Note: ET-PKD521B will be available from CY2022 3Q.
- Lens Fixed Attachment**  
ET-PLF10 (For ET-D3LEF70) / ET-PLF20 (For ET-D3LEU100/LEW200)  
Note: This attachment may be required in some installation environments.
- Stepping Motor Kit** ET-D75MKS10  
Note: Calibration is required each time the lens is mounted.
- DIGITAL LINK Switcher / Digital Interface Box**  
ET-YFB200G / ET-YFB100G  
Note: Requires TY-SB01DL DIGITAL LINK Terminal Board LINK (available from CY2022 3Q). ET-YFB200G / ET-YFB100G not compatible with 4K signals.
- Wireless Module** AJ-WM50 Series  
Note: Product availability may vary by country or region. The suffix at the end of the model number is omitted. Operating Temperature: 0–40 °C (32–104 °F).
- Early Warning Software** ET-SWA100 Series  
Note: Part number suffix may differ depending on the license type.
- NFC Upgrade Kit** ET-NUK10  
Note: Product availability may vary by country or region.
- Wireless Presentation System PressIT**  
TY-WPS1 (basic set)  
Visit <https://panasonic.net/cns/prodisplays/pressit> for more information.
- Function Boards**  
12G-SDI Terminal Board  
TY-SB01QS  
Wireless Presentation System Receiver Board  
TY-SB01WP  
DIGITAL LINK Terminal Board  
TY-SB01DL  
Note: Available from CY2022 3Q.



Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Availability of products and accessories may vary by country or region. Products may be subject to export control regulations. DLP, DLP logo, and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. Windows® is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Intel and the Intel logo are trademarks of Intel Corporation or its subsidiaries. SOLID SHINE and PressIT are trademarks of Panasonic Holdings Corporation. All other trademarks are the property of the respective trademark owners. © Panasonic Connect Co., Ltd. 2022. All rights reserved.



For more information about Panasonic projectors, please visit:  
Projector Global Website – <https://panasonic.net/cns/projector/>  
Facebook – [www.facebook.com/panasonicprojectoranddisplay](https://www.facebook.com/panasonicprojectoranddisplay)  
YouTube – [www.youtube.com/user/PanasonicProjector](https://www.youtube.com/user/PanasonicProjector)

Note: Following the shift of the Panasonic Group to a holding company system, the Connected Solutions Company of the Panasonic Corporation has changed to Panasonic Connect Co., Ltd. as of April 1, 2022.

All information included here is valid as of August 2022.

PT-RQ25KPRE5 Printed in Japan.