

DL22A Digital Podium

Professional Podium

The DL22A is designed to be cost-effective solution compared to DL23B. It is convenient for short speeches like at small, press or hotel conference rooms. It is easy to connect your projector and sound systems to DL22A.

DL22A

- 22" top screen with IR touch technology
- Professional microphones
- Simple functional design
- Metal body
- Multiple color options
- Built-in high performance PC.



The touch screen is designed with IPS Technology to prevent picture loss during angle change. Large display size makes the various documents to read easy.



On/Off buttons and easily accessible communication connectors to transfer files into built-in PC.



Easy to connect audio and video systems (ex. projector) from bottom connectors.



22" FullHD Front Panel



The front screen is designed based on IPS Technology to prevent picture loss during angle change.

Technical Specifications

Main Specifications	
Lecturer Screen	22" Multi touch capacitive
Front Screen	22" with built-in signage media player
Built-in PC for Speaker Screen	intel i3 4GB Ram, 120 SSD, Win 10 Embedded IoT
Microphone	2 pcs 18" Gooseneck Condenser Microphone
Lifting Column	Available
Front Panel	
Resolution	1920x1080FHD
Brightness	250 cd/m2
Aspect ratio	16:9
Panel Type	IPS
Front Panel Player	Built-in Digital Signage Media Player
Front Panel Content Management Software	Available
Lecturer Panel	
Resolution	1920x1080 FHD
Brightness	250 cd/m2
Aspect ratio	16:9
Touch Screen Technology	Capacitive
Touch Points	10 points
Lecturer Panel PC Specifications	
CPU	4th Generation Intel Core i3
RAM	4 GB DDR4
HDD	120 GB SSD
Operating System	Windows Embedded 10 IoT
Microphone	
Length	18"
No of microphone	2 pcs
Output Connector	3-way XLR (Male)
Microphone Type	Cardioid
Frequency Response	50 -18 kHz
Sensitivity (at 1,000Hz)	-60dB ± 3dB
Impedance	220Ω
Power ON indicator	LED
Power requirement	2xPhantom Power (48V)
Inputs (on Speaker Panel)	
230V Plug (Max 5A)	
USB	USB 2.0 X 4 (for internal PC)
Outputs (Bottom of Podium)	
VGA	Available
HDMI	Available
Ethernet	Available
XLR for microphone	Available
USB	USB 2.0 X 4 (for internal PC)
Power	
Power Input	230V 50Hz
Power Consumption	450W (max)
Peripherals & other features	
Clock & Timer	Available
Color	Black speaker panel and base, gray body
Packing	Wooden box export packing
Mechanical Specs	
Outline Dimension (mm)	Set: 550 x 800 x 1091
	Package: 670 x 920 x 1300
	Set: 68 kg
	Package: 107 kg
Optional features	Front screen PC
	Flight case

Mechanical Specifications

