

WIRELESS MICROPHONES

iLive UHF Wireless Microphone Systems

iLive 1 true diversity wireless microphone systems

iLIVE 1 LAVALIER

iLive 1 lavalier true diversity wireless microphone system with 32 selectable channels, automatic channel targeting and synchronization with automatic frequency selection. The microphone signal receiver, body pack transmitter with lavalier microphone and jack/jack cable are included in each set. Very stable signal transmission and reception, choice of selectable channel frequencies allows the use of the microphones in a various environments without any distortion.



Technical Specifications	iLIVE 1 receiver
Power supply	12-15 V DC, 1.25 A
Output	Balanced XLR, unbalanced 6,3 mm TS JACK
Receiver way	Two frequency conversion super-heterodynes
Intermediate frequency	10,7 MHz
Antenna	BNC
T.H.D	< 0,7 %
Sensitivity	6 dB μ V
Image rejection	36 dB
Max. audio output	0 dB
Dimensions (H x W x D)	45 mm x 210 mm x 206 mm
Weight	1.4 kg
Material	Steel enclosure, aluminum front panel

Technical Specifications	iLIVE 1 body pack transmitter
Carrier frequency range	606 MHz - 621 MHz
Modulation	FM
Channels	32
Audio frequency response	45 Hz - 18 kHz
S/N ratio	> 105 dB
Antenna	1/4 wave antenna
Input connector	4 pin mini XLR connector
Transmitter's power	15 mW
Working range	90 m (Note: actual range depends on RF signal absorption, reflection and interference)
Polar pattern	Cardioid
Battery	2 x 1,5 V AA Alkaline battery
Dimensions (H x W x D)	110 mm x 64 mm x 25 mm
Weight	165 g
Material	Plastic

Technical Specifications	iLIVE 12 LM
Capsule type	Condenser
Impedance	200 Ω
Sensitivity	-46 dB
Frequency	50 Hz - 18 kHz
Connectors	4 pin mini XLR connector
Phantom power voltage	5 V
Cable length	1 m
Weight	21 g
Colour	Black RAL9017
Accessories	Windscreen