# BrightSign<sup>®</sup> XD5

Exceptional performance with scalability in mind.

BrightSign XD5 is a dependable PC alternative, delivering high-performance 2D motion graphics and stunning 4K video with versatile connectivity options for efficient, expandable, and engaging deployments.

Immersive Engagement

Dynamic and responsive interactions.



- Responsive multi-touch
  engagement
- · Immersive sensor & light controls
- Robust 2D motion graphics



Centerpiece

**Visuals** Stellar 4K visual

- Striking 4K60p video
- Dual video decoding
- Full HD video rotation

Interactive Journeys

Versatile and unique experiences.



- · Personalized engagement
- Usage tracking & analytics
- Measurement & data integrations

#### Cohesive Communications

Simplified and streamlined signage.



- Live 2D data animations
- 4K IP Streaming
- Power over Ethernet



## XD235

#### Standard I/O Package

Seamless 2D motion graphics and pristine 4K video playback, complemented by PoE+ and the option of secure SSD storage.

## XD1035

#### Expanded I/O Package

Expands connection and engagement options with serial and dual USB ports.



# The BrightSign XD5 Advantage

- · Avoid PC hassles and reliably engage audiences with interactive data-driven animations
- Enhance visual experiences with stellar 4K or dual HD video, ideal for on-screen and projected displays
- · Streamline setups and resources with a slim, energy efficient player powered over Ethernet
- · Unlock possibilities with an expandable platform of connections and a secure, self-encrypting SSD storage option
- Operate with unparalleled reliability, security, and sustainability on BrightSignOS™
- · Reduce total cost of ownership with complimentary remote player management and controls
- · Achieve CMS choice flexibility with a trusted global network of leading integrated partner solutions

# **BrightSignOS™**

#### The power of purple.

The only purpose-built operating system that brings unrivaled reliability, security, signage power and sustainability to every BrightSign player.



- **Unrivaled security** that reduces risk to near zero with purpose-built file system designed to remove vulnerabilities and only runs signage.
  - · Exceptionally protected operating system with a secure digital signature
  - · Runs a singular signage application to protect against viruses
  - · Configurable to any type of security profile
  - Security extends to integrated CMS solutions



- Legendary reliability with unmatched uptimes and a lower total cost of ownership.
- Persistent self-healing protocols resulting in unmatched uptimes
- Secure built-in remote player management and monitoring
- · Remote diagnostics and controls to reduce costly on-site visits
- · Removable storage that avoids rip/replace situations



RELIABLE

SUPERIOR



Superior signage performance for simple to sophisticated experiences.

- Integrated with hundreds of global CMS solutions
- Highly extensible to securely run specialized signage technologies




**Unmatched sustainability** through updates that stay ahead of market demands.

- Low power requirements with high performance
- Guaranteed long life cycle support for unprecedented longevity
- · Free updates applied on-demand and consistent across hardware generations
- Remote re-provisioning at any time to ensure flexibility

# Invest in BrightSignOS to achieve long-term success

#### Designed to reduce risk and save on signage.

Downtime is the most expensive investment in signage that often gets overlooked. Failure doesn't happen at implementation, it happens after. BrightSignOS<sup>™</sup> is designed to solve and mitigate ongoing risks to avoid rip and replace situations resulting in huge savings throughout the long life of your player.



# **Hardware Specifications**



(Internal)

M.2 PCIe for optional NVMe SSD storage

Locking Power (12v/3A)

• USB Type C port: supports high-speed host mode & provides 5V/1A power to peripheral devices

54

- USB Type A port: provides 5V/1A power to peripheral devices
- GPIO port: 8 bi-directional GPIOs
- Audio port: supports analog & SPDIF digital

• Real time clock: 14-day life

# **Software & Services**

#### **BSN.**Cloud

A scalable cloud infrastructure that securely connects BrightSign players to a suite of integrated services for remote device, content, and network management.

#### **bsn.**Control

Free remote player monitoring and control service with a choice of CMS.

#### **bsn.**Content

Paid CMS service for cloud-based content, network and user management.

#### Partner CMS Solutions

Flexible choices with seamless player integrations

#### BrightAuthor: connected

Free software to provision players, access BSN.Cloud services, and connect to a variety of partner CMS solutions.

**BSSN.COLO** bsn.Control bsn.Content

PoE+Gigabit Ethernet

E Key M.2 for optional WD-105 module

# **Technical Specifications**

	XD235	XD1035
I/O Package	Standard	Expanded
VIDEO & HTML5 ENGINES		
4K video decoding	X 8-bit at 60p 10-bit at 30p	X 8-bit at 60p 10-bit at 30p
Full HD at 60p video decoding	X (dual)	X (dual)
HD images & graphics	Х	Х
HTML5 Performance	Smooth full screen 2D WebGL motion	Responsive multi-touch 2D WebGL
HTML support: HTML5, CSS, JavaScript, SVG, WebGL, and Chromium compatible	Х	×
MEDIA FORMATS		
4K Video codecs: H.265/HEVC, H.264/AVC (max 30p), VP9	X H.265 at 60p H.264 at 30p	X H.265 at 60p H.264 at 30p
4K Video Containers: MP4, .MOV, .MKV, .WEBM, .TS, .MPG, .MPEG, .PS, .M2P, .MPV, .AVI, .HEVC, .H264, .AVI, .VP9, and .MJPG	Х	X
Full HD Video Codecs: H.265/HEVC, H.264/AVC, VP9, MPEG 4 part 2, MPEG1 video, MPEG2 video	Х	X
Full HD Video Containers: MP4, .MOV, .MKV, .WEBM, .TS, .MPG, .MPEG, .PS, .M2P, .MPV, .AVI, .HEVC, .H264, .AVI, .VP9, and .MJPG	Х	Х
Images: BMP, JPEG, PNG	Х	Х
Audio: MP2, MP3, AAC and WAV (AC3 is passed through)	Х	Х
DISPLAY RESOLUTIONS		
Supports all common screen resolutions up to 4K	Х	Х
Supports <u>additional</u> & <u>customizable</u> display resolutions with unique aspect ratios	Х	Х
ACCESSORIES		
BP200 & BP900 USB Button Pads		Х
WD-105 Dual Antenna Wireless/Bluetooth Module	Х	Х
MicroSD Class 10 Cards (various capacities)	Х	Х
256GB PCIe NVMe M.2 SSD	Х	Х
BrightSign Mobile USB Modem & Service		Х
MISCELLANEOUS		
Operating Temperature Range	0°C to 50°C	
Dimensions (W x D x H)	205 x 185.9 x 19.2mm	
Shipping Weight / Player Weight	1.3 kg / 0.59 kg	
Locking Power Supply	12V / 3A	
Multi-Country Power & Regulatory Approvals	Х	Х
Built-in Wall Mounting	Х	Х
1 Year Warranty, parts and labor*	Х	Х
MSRP	\$600	\$700

\*2 year warranty, parts and labor, for units shipped from an EU or UK distribution center and to an EU or UK address.

Contact us at <u>sales@brightsign.biz</u> <u>www.brightsign.biz</u> Copyright © 2024 by BrightSign, LLC. All rights reserved.