

[Click to Print This Page](#)



E-VISION 15000i 4K+

THE VISIONARIES CHOICE



E-Vision 15000i 4K+ (Preliminary)

15,000 ISO / 13,500 ANSI Lumens | Contrast Ratio: 20,000:1 (Dynamic Black) | Part Number: 124-369

Key Specifications:

Colour System:	Laser Phosphor with Colorboost (Red Laser). Phosphor wheel: 2 x 7200rpm (120Hz) Colour wheel: 8 Segment RGBYRGBY 2 x 7200rpm (120Hz)
Display Type:	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
DMD Specification:	1920 x 1200 pixels native display. (3840 x 2400 via 4-way pixel shift technology) Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	Video & Graphics Processing • Nexus electronics platform • HDMI 2.0 • DisplayPort 1.2 • 10-bit colour processing (30-bits per pixel) 1,073,741,824 colours • Hue, Saturation and Gain colour management. • 24p and 1080p native display. • HDR support • Input source automatically detected • Selectable Dynamic Black • DICOM simulation mode

- Optics engine sealed to IP6X

Geometry Correction

- Vertical & Horizontal Keystone correction
- Four Corner adjustment
- Rotation -100 to +100 with +/- 0.25° per step
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 / 16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled
- Digital Zoom 0% ~ 100%
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens. 16:10 / 16:9 / 4:3 / 2.35:1
- Custom warp

Edge Blending

- Correction for non-active pixels at the edge of the display.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® Includes Ethernet 100BaseT and RS232/IR control.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector LAN Control

- Free Digital Projection Projector Controller II software
- Intuitive user interface for network control.
- At-a-glance monitoring of projector status.
- Simultaneous control of user-defined groups of projectors.

Source Compatibility

12G-SDI, Supports a high data transfer rate of up to 12 gigabits per second (Gbps), enabling the transmission of uncompressed 4K UHD (Ultra High Definition) video signals with a single connector

Graphics standards up to WUXGA 1920 x 1200 - 120Hz RB, Up to WQXGA 2560 x 1600 60Hz RB (DisplayPort)

Video standards including HDTV 1080p - 60Hz and 4K-UHD (3840 x 2160) 60Hz

Support for up colour gamut up to P3

Inputs/Outputs

Video & Computer		
Type	Connector	Qty
HDMI 2.0 (HDCP compatible)	HDMI	2
DisplayPort 1.2	DisplayPort	2
HDBaseT	8P8C "RJ45"	1
12G-SDI in	BNC	1
3G-SDI out	BNC	1

	Communication & Control		
	Type	Connector	Qty
	3D Sync In	BNC	1
	3D Sync Out (loop through)	BNC	1
	3D Sync Out for IR	BNC	1
	LAN / Art-Net	EtherCON RJ45	1
	HDBaseT/Ethernet/RS232/IR	RJ45	1
	Serial In RS-232C	9-pin D-Sub	1
	Serial Out RS-232C	9-pin D-Sub	1
	Wired Remote In	3.5mm Stereo Jack	1
	Wired Remote Out	3.5mm Stereo Jack	1
	12V Trigger 12V.350mA	3.5mm Stereo Jack	1
	USB Power out 5V/2A	USB Type A	1
3D Formats Supported	Off Auto Side by Side Top and Bottom Dual Pipe Frame Sequential		
HDTV Formats Supported	EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), 4K-UHD (3840 x 2160), DCI 4K (4096 x 2160)		
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, WQXGA		
Bandwidth			
Remote Control	Infrared/Wired Remote Control Unit		
Automation Control	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control		
Colour Temperature	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native)		
Operation			
illumination Type	Laser Phosphor. ECO mode support (80% Brightness)		
Typical illumination Life	20,000 hours		
Lenses	Lens	Part No.	Optimised Focus Range*
	0.31 - 0.33 :1 UST zoom (90° Type)	124-318	TBD
	0.55 - 0.75 :1 zoom	124-319	2.03m - 7.62m
	0.74 - 1.08 :1 zoom	124-320	1.52m - 10.16m
			Lens Shift (Frame)
			Vert: 0.5 (U) 0.5 (D) frame, Hor: None (L) None (R) frame
			Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
			Vert: 0.5 (U) 0.5 (D)

			(mech 1.27m - 12.7m)	frame, Hor: 0.15 (L) 0.15 (R) frame
	1.05 - 1.41 :1 zoom	124-321	1.52m - 12.7m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
	1.4 - 2.11 :1 zoom	124-322	1.52m - 12.7m (mech 1.27m - 15.24m)	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
	2.1 - 4.0 :1 zoom	124-323	1.52m - 12.7m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
	3.0 - 4.52 :1 zoom	112-503	TBD	Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
	4.46 - 6.94 :1 zoom	112-504	TBD	Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.2 (L) 0.2 (R) frame
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,			
Lens Mount	Centred lens for installation flexibility Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	990W (max)			
Thermal Dissipation	TBD			
Fan Noise	Normal mode: 40 dBA typical Eco Mode: Max 39 dBA			
Operating/Storage Temperature Operating:	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)			
Operating Humidity	90% (with maximum temperature of 35°C (95°F))			
Weight	29.4 kg / 64.8 lbs			
Dimensions	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch			
Safety & EMC Regulations	TBD			
Accessories				
	Accessory		Part No.	

**Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings
User Guide	



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION

Specifications subject to change without notice.
©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629
ISO 9001