



TITAN LASER SERIES DIGITAL PROJECTORS

THE VISIONARIES CHOICE



Titan 41000 4K-UHD (Preliminary)


41,000 ISO / 36,000 ANSI @ 4K-UHD. 45,000 ISO / 42,000 ANSI @ WUXGA Lumens | Contrast Ratio: 18,000:1 (Dynamic Black) / 2,000:1 Native | Part Number: 121-654

Key Specifications:



Colour System:	Laser Phosphor with ColorBoost+Red Laser
Display Type:	3 x 0.96" WUXGA DMD™
DMD Specification:	Display capability up to 4K-UHD 8.3 megapixels on screen at 4K-UHD Fast transit pixels for smooth greyscale and improved contrast. Display capability up to 4K-UHD (3840x2160)
Aspect Ratio:	16:9
Fill Factor	N/A as Smooth Picture DMD
Key Features:	Video & Graphics Processing <ul style="list-style-type: none">• HDMI 2.0 compliance for Side by Side, Frame Packing, Frame Sequential and TopBottom 3D Formats.• DisplayPort 1.2 with HDCP 2.2 compliance.• 10-bit colour processing (30-bits per pixel).• Support for 1080p 24Hz native display.• Support for 4K 4096 x 2160 resolution.• HDR support• Input source automatically detected.• Input redundancy mode with auto switching.• Dual Pipe Processing: Two sources in parallel for Left and Right eyes.• Synchronisation of active 3D glasses or polarising switcher.• DICOM simulation mode.• Sealed light engine General Features


	<ul style="list-style-type: none"> • Constant Brightness control • Multi Projector brightness and colour control. • Compatible with selected 3rd party lenses via lens converter • Selectable EDID • Custom Start-up Logo • Smear Reduction (fast frame) (2D Only) • Electronic PIC MUTE with selectable fade in/out timers • On board 4 -line LCD display for at a glance status <p>Geometry Correction</p> <ul style="list-style-type: none"> • Vertical & Horizontal Keystone correction. • Four Corner adjustment. • Rotation. • Pin/Barrel. • Wall Corner adjustment. • Centre Shift (Horizontal and Vertical linearity adjustment). • Custom Warp. • Upload of maps for warp, blend, uniformity and masking. • Selectable aspect ratios: 5:4 / 4:3 / 16:10 /16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled. • Digital Zoom. • Blanking control for custom input window sizing. <p>Edge Blending</p> <ul style="list-style-type: none"> • Blending control available for all sides with width control. • Correction for non-active pixels at the edge of the display. • Electronic Black Level Compensation. • Upload of Blend Maps including Blend, Uniformity, Masking, Pixel by Pixel <p>HDBaseT® Interface</p> <ul style="list-style-type: none"> • Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable • Allows projector to be placed up to 100m from source with low cost cabling • Supports up to 4K 4096 x 2160@60Hz 4:2:0 or 4K 4096 x 2160@30Hz 4:2:2 • Includes Ethernet 100BaseT and RS232/IR control. <p>Colour Processing</p> <ul style="list-style-type: none"> • Four colour modes available • Powerful seven point colour correction for accurate colour matching with presets. • Easy colour temperature selection • Manual seven point colour adjustment • Traditional lifts and gains <p>Projector Controller Software</p> <ul style="list-style-type: none"> • Intuitive user interface for network control • Simultaneous control of user-defined groups of projectors • At-a-glance monitoring of projector status <p>Projector Automation</p> <ul style="list-style-type: none"> • Real-time clock provides daily on/off automation • E-mail alerts for system status <p>Installation</p> <ul style="list-style-type: none"> • 4 x eye bolts fitted for easy rigging. • 4 x top stacking mounts and mount securing pins supplied as standard accessories.
Source Compatibility	<p>2D Graphics standards up to 4K-UHD 3840x2160 resolution at 60Hz via HDMI 2.0b, HDBaseT (4:2:0), DisplayPort inputs</p> <p>3D Graphics standards up to dual-pipe WUXGA 60Hz for input (120Hz output) via HDMI 2.0 and Display Port inputs</p> <p>12G-SDI is SMPTE 259M, 292M, 424M and ST-2082 compliant.</p>

	WUXGA mode 2D sources up to WUXGA 60Hz and 4K-UHD 60Hz can be displayed scaled to fit WUXGA 3D sources up to WUXGA 60Hz Input -120Hz output can be displayed scaled to fit WUXGA 4K-UHD mode 2D sources up to 4K (4096 x 2160) will be displayed scaled to fit 4K-UHD Auto Mode Sources greater than WUXGA will be displayed scaled to fit 4K-UHD		
Inputs/Outputs	Video & Computer		
	Type	Connector	Qty
	DisplayPort 1.2a (2D)	DisplayPort	2
	HDMI 2.0b	HDMI	2
	12G-SDI in	BNC	1
	12G-SDI out	BNC	1
	HDBaseT/LAN	RJ45	1
	.		
	Communication & Control		
	Type	Connector	Qty
	3D SYNC IN	BNC	1
	3D Sync Out	BNC	1
	LAN	RJ45	1
	RS-232	9-pin D-Sub	1
Wired Remote	3.5mm Stereo Jack	1	
12V Trigger	3.5mm Stereo Jack	1	
3D Sync IR Out	BNC	1	
USB 5V 2A	Type A	1	
3D Formats Supported	Sequential / 1080P/WUXGA @100Hz Sequential / 1080P/WUXGA @120Hz Dual-Pipe / 101080P/WUXGA80p @ 50Hz per eye Dual-Pipe / 1080P/WUXGA @ 60Hz per eye Also supports mandatory formats including side by side, top/bottom and frame packing		
HDTV Formats Supported	1080p (23.98Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 59.94Hz, 60Hz). 1080i (50Hz, 59.94Hz, 60Hz). 720p (50Hz, 59.94Hz, 60Hz). 4K-UHD (23.97Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 60Hz).		
Computer Compatibility	2D 4K-UHD up to 60Hz 3D Supported Formats will be displayed up to WUXGA		
Bandwidth	18Gb/s (600MHz clock rate) on HDMI		
Remote Control	Addressable IR remote Control, Wireless and wired. On-Board keypad		
Automation Control	LAN RS-232 Alert E-Mails from Projector Served webpage OSD functions for full Projector Control via web browser LAN Control-Crestron Roomview™ LAN Control-Crestron eControl LAN Control-PJ Link compatible LAN Control-AMX SSDP LAN to RS232 (RS232 by Telnet) Concurrence Control for RS232/LAN DMX Art-Net control Scheduled On and Off times		
Colour Temperature	3200K to 9300K		

Operation																																											
Illumination Type	Laser Light Source																																										
Typical illumination Life	20,000 Hours (Normal Mode) 40,000 Hours (ECO Mode)																																										
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.37:1 (Right Angled)</td><td>120-510</td><td>1.6m - 4.9m</td><td>Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.31 (L) 0.31 (R) frame</td></tr><tr><td>0.65-0.85:1 (Right Angled)</td><td>120-511</td><td>2.8m - 8.4m</td><td>Vert: 0.62 (U) 0.62 (D) frame, Hor: 0.25 (L) 0.25 (R) frame</td></tr><tr><td>0.8-1.16:1 (Includes support bracket)</td><td>120-827</td><td>1.7m - 11m</td><td>Vert: 0.51 (U) 0.51 (D) frame, Hor: 0.20 (L) 0.20 (R) frame</td></tr><tr><td>1.16 - 1.49:1 zoom HB</td><td>109-236</td><td>3m - 15m</td><td>Vert: 0.50 (U) 0.408 (D) frame, Hor: 0.2 (L) 0.2 (R) frame</td></tr><tr><td>1.39 - 1.87:1 zoom HB</td><td>105-610</td><td>4m - 24m</td><td>Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame</td></tr><tr><td>1.87 - 2.56:1 zoom HB</td><td>105-611</td><td>4m - 24m</td><td>Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame</td></tr><tr><td>2.56 - 4.16:1 zoom HB</td><td>105-612</td><td>9.1m - 45m</td><td>Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame</td></tr><tr><td>4.16 - 6.96:1 zoom HB</td><td>105-613</td><td>12m - 80m</td><td>Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame</td></tr><tr><td>6.92 - 10.36:1 zoom HB</td><td>109-235</td><td>12m - 80m</td><td>Vert: 0.65 (U) 0.45 (D) frame, Hor: 0.28 (L) 0.28 (R) frame</td></tr></table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/-2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.37:1 (Right Angled)	120-510	1.6m - 4.9m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.31 (L) 0.31 (R) frame	0.65-0.85:1 (Right Angled)	120-511	2.8m - 8.4m	Vert: 0.62 (U) 0.62 (D) frame, Hor: 0.25 (L) 0.25 (R) frame	0.8-1.16:1 (Includes support bracket)	120-827	1.7m - 11m	Vert: 0.51 (U) 0.51 (D) frame, Hor: 0.20 (L) 0.20 (R) frame	1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.50 (U) 0.408 (D) frame, Hor: 0.2 (L) 0.2 (R) frame	1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame	1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame	2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame	4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame	6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.65 (U) 0.45 (D) frame, Hor: 0.28 (L) 0.28 (R) frame
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																																								
0.37:1 (Right Angled)	120-510	1.6m - 4.9m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.31 (L) 0.31 (R) frame																																								
0.65-0.85:1 (Right Angled)	120-511	2.8m - 8.4m	Vert: 0.62 (U) 0.62 (D) frame, Hor: 0.25 (L) 0.25 (R) frame																																								
0.8-1.16:1 (Includes support bracket)	120-827	1.7m - 11m	Vert: 0.51 (U) 0.51 (D) frame, Hor: 0.20 (L) 0.20 (R) frame																																								
1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.50 (U) 0.408 (D) frame, Hor: 0.2 (L) 0.2 (R) frame																																								
1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame																																								
1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame																																								
2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame																																								
4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.65 (U) 0.65 (D) frame, Hor: 0.28 (L) 0.28 (R) frame																																								
6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.65 (U) 0.45 (D) frame, Hor: 0.28 (L) 0.28 (R) frame																																								
Lens Mount	Motorised Shift, Zoom and Focus. Intelligent Lens Memory with 10 user-definable pre-set positions for zoom lenses.																																										
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet																																										
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes																																										
Power Requirements	110V~130Vac/ 50~60Hz 180V~240Vac/ 50~60Hz single phase * Note that in 120V operation, the projector will be at ~25% brightness																																										
Power Consumption	230V Typical: 3650W , Maximum 4000W																																										
Thermal Dissipation	Max 14160.38 BTU/hr @ 200VAC Max 3685 BTU/hr @ 110VAC																																										
Fan Noise	Max 54 dBA Eco Typ : 53 dBA (TBC)																																										

Operating/Storage Temperature:	Operating: Full Power 0°C ~ 35°C (32°F ~95°F), ECO upto 40°C (104°F) Storage: -20°C ~ 60°C (-4°F ~ 140°F)	
Operating Humidity	Operating: 10% ~ 90% non-condensing Storage: 10% ~ 90% non-condensing	
Weight	88 (without lens) kg / 194 (without lens) lbs	
Dimensions	L: 840mm, W: 650mm, H: 381mm (Excl handles) L: 33.1in, W: 25.6in, H: 15in (Excl handles) * See drawings for full details	
Safety & EMC Regulations	TBC	
Accessories		
	Accessory	Part No.
	Infrared Remote Control (Replacement)	118-678
	*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.	
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings	
User Guide	User Guides User Guides (German) User Guides (French) User Guides (Korean) User Guides (Japanese) Laser Risk Group Document Important Information Ultra Short Throw Lens Installation Guide	

 **DIGITAL PROJECTION, LTD**
 **Unit 3, Aniseed Park, Broadgate,**
Oldham, UK OL9 9XA

 **T: +44 (0)161 947 3300**

 **www.digitalprojection.com**

 **DIGITAL PROJECTION, INC**

 **55 Chastain Road, Suite 115 Kennesaw, GA. 30144**

 **T: 770.420.1350 | F: 770.420.1360**

DIGITAL  **PROJECTION**

Specifications subject to change without notice. ©2024 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

A brand of 



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029, PR
China



T: +86.10.58239771 | F: +86 10 58239770