


4K PTZ Camera

AMC-G403



- ① USB 3.0
- ② LINE IN
- ③ LAN
- ④ DC 12V

Features

- 1/2.8" CMOS, 8.46MP;
- 3x optical zoom, up to horizontal 81°FOV;
- 6x lossless zoom at 1080P30 resolution;
- USB 3.0 support 4K video output;
- Support standard UVC/UAC protocol;
- Ethernet support H.265/H.264 video compression, up to 4K video output;
- Ethernet and USB 3.0 outputs;
- Dual stream.

Technical Data

Camera

Image Sensor

1/2.8" CMOS, 8.46MP

Optical Zoom

3x

Focal Length

f=3.3mm ~ 9.7mm

Iris

F2 ~ F3.7

HFOV

81.4° ~ 31.3°

Digital Zoom

5x

Focus System

Auto, Manual, PTZ Trigger, One Push Trigger

Shutter speed

1/50 ~ 1/10,000s

AGC

Auto, Manual

White Balance

Auto, Manual, Auto Tracking, One Push, Specified Color Temperature

BLC

Support

Wide Dynamic

Support

Exposure

Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority

SNR

≥50dB

PTZ

Pan

-170°~+170°; 0.1°~120°/s

Tilt

-30°~+90°; 0.1° ~ 90°/s

Image Filp

Support

Preset Number

256

General

Power

DC12V; <12W

Operating Temperature

0°C ~ +40°C

Storage Temperature

-20°C ~ +60°C

Dimensions (L*W*H)

176mm × 137mm × 171mm

Weight

≤1.2kg

Interface

Network

1 × RJ45:1×10M/100M

1. Image Compression:

H.264/H.265:

4KP30/P25,

1080P60/P50/P30/P25,

720P60/P50/P30/P25

2.Protocol:

ONVIF/RTSP/RTMP/TCP/UDP/SRT/RTMPS/GB28181

3. Audio Compression:

AAC/G.711

4. Supports Multi-Streams

USB 3.0

1. Support UVC1.1

2. UVC Support:

H.264/H.265/MJPEG:

4KP30/P25, 1080P30/P25,

720P30/P25

YUY2/NV12: 1080P30/P25,

720P30/P25

3. UAC Audio Format PCM

Audio

1 × LINE IN, 3.5mm