

NovoTouch BK863i

EDLA Certified, True 86" 4K-UHD interactive display with wireless collaboration and touch interaction



Features

Hardware

- 86" display with ultraHD 4K (3,840 × 2,160) resolution for outstanding details and stunning visuals
- 3mm-thick toughened glass for added protection against scratches or screen damage
- Front bezel USB-A, USB-C ports for quick connection to USB keyboards/mice, memory drives and data
- High-speed Wi-Fi 6 connection
- Dual RJ45 ports for easy Ethernet expansion

Software

- Built-in whiteboard and NovoConnect screen sharing Apps to facilitate efficient collaboration in meeting rooms and classrooms
- Screen annotation and recording tools available for easy content sharing
- Centralized device management through Remote Manager Cloud or Windows software, simplifying IT administration

Display	Type/Technology		Backlit D-LED (ADS Panel)
	Panel Size		86"
	Brightness (Typ)		450cd/m2
	Contrast Ratio (Typ)		1,200:1
	Native Resolution		4K Ultra-HD (3840 x 2160)
	Viewing Angle (H/V)		178°/178°
	Aspect Ratio		16:9
	Response Time (ms)		8ms (Typ)
	Refresh Rate (Hz)		60Hz
	Estimated Life Time (Typ)		50,000 hours (Min)
	Display Color (Bit)		1.07 billion (10-bit)
	Installation Orientation		Landscape
	Daily Operation (Hours/Days)		16/7
	Technology		Infrared Touch
Interactivity	Touch Points	Writing	10 Point (Standard)
		Touch	40 Point (Standard)
	Accuracy	Finger	±1mm (Over 90% area)
		Passive Pen	±1mm (Over 90% area)
	Response Time		<5ms
	Touch Resolution		32,768 x 32,768
	Surface Protection		3mm Anti-Glare Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
Operating System	Touch Tools		Finger, Stylus, Glove, Opaque Objects
	System Version		Android™ v14.0
	CPU		Multi-Core High-Performance ARM®CPU
	GPU		Mali™ G52
	RAM		8GB DDR4
	Internal Storage		64GB (eMMC Flash) (About 25GB User Availability)
Connectivity	Input	Display	HDMI v2.0 (x1) Side HDMI v2.0 (x1) Front USB-C (x1) Front (up to PD 15W charging)
		Audio	Line-Out (3.5mm) (x1)
	Output		HDMI-Out v2.0 (x1) (up to 4K@60Hz)
	Internet		LAN (RJ45) (x1) (10/100/1000 Mbps)
	Control		RS232-In (x1)
	Wireless	WiFi	IEEE802.11ax (2.4GHz/5GHz)
		Bluetooth	BT 5.2
	USB-A	I/R Receiver	Front (x1) (±25° Angle, >8m Distance)
		Front	USB 3.0 (x2)
	USB-B	Side	USB 2.0 (x1)
		Front	USB Type B (x1) (For Touch Port)
	USB-C	Side	USB Type B (x1) (For Touch Port)
		Front	USB-C (x1) (15W charging & display input)
Expansion	Windows Module (Option)		Standard Intel 80pin OPS (Option)
Audio	Speakers		18W (x2) (Stereo)
Power	Power Supply (Internal)		AC 100 - 240V, 50/60Hz (5.5A)
	Consumption		≤450W
	Standby Mode		≤0.5W (Standby)
Physical Characteristics	VESA Mounting (FPMPI)		4 - M8 × 25mm, 800 x 400mm
	Mini PC VESA Mount		100 x 100mm
	Dimension (L x H x D)		1953.0x90.2x1172.3
	Weight		63kg
	Color		Silver
Accessories	Standard		AC Power Cord, Stylus (x2), Remote Control (w/Batteries), Wall Mount Kit, HDMI Cable (3M), Touch Cable (3M) Documentation Kit
	Optional		Windows OPS Module – Standard 80pin

©2025 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.